

View Online at <https://aerobasegroup.com/nsn/2920-01-298-5738>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.712 inches and 0.732 inches

**Second Step Diameter:**

0.780 inches

**Keyway Width:**

0.188 inches

**Unthreaded Portion Length:**

Between 1.248 inches and 1.268 inches

**Mounting Hole Thread Direction:**

Right-hand

**Mounting Style:**

Bracket mtd w/three mtg holes, top hole threaded

**Keyway Length:**

1.020 inches

**Submersibility:**

Nonsubmersible

**Shaft Rotation Direction:**

Clockwise or counterclockwise

**Distance From End To Keyway Center:**

Between 1.336 inches and 1.366 inches

**Thread Diameter:**

0.750 inches

**Shaft Drive End Style:**

Straight shaft end, threaded, w/keyway

**Distance Between Shaft Center And Bottom Mounting Hole Center:**

5.200 inches

**Distance Between Shaft Center And Top Mounting Hole Center:**

5.200 inches

**Angular Deviation Of First Hole From Top Center In Deg:**

0.0

**Angular Deviation Of Second Hole From First Hole In Deg:**

10.0

**Distance Between Inside Surfaces Of Hinge Bracket:**

Between 7.292 inches and 7.402 inches

**Distance Between Outside Surfaces Of Hinge Bracket:**

Between 7.920 inches and 8.030 inches

**Bottom Mounting Hole Diameter:**

Between 0.440 inches and 0.462 inches

**Thread Series:**

Unf

**Thread Class:**

2a

**Mounting Hole Thread Series Designator:**

Unc

**Mounting Hole Thread Diameter:**

0.375 inches

**Mounting Hole Thready Qty Per Inch (tpi):**

16

**Mounting Hole Thread Class:**

2b

**Thready Qty Per Inch (tpi):**

16

**Voltage In Volts:**

28.0

**Special Features:**

USED-ON-235-0010

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A14700