

View Online at <https://aerobasegroup.com/nsn/2920-01-420-9968>

Thread Direction:

Right-hand

Keyway Width:

Between 0.250 inches and 0.251 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Environmental Protection:

Fungus resistant

Keyway Length:

Between 0.990 inches and 1.000 inches

End Application:

2320-01-380-8604; weapon system e/i truck, vehicle system, 1 1/4-ton (hmmwv)

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Thread Diameter:

0.750 inches

Maximum Output Current Rating In Amps:

200.0

Grounding Method:

External

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

5.200 inches

Distance Between Shaft Center And Top Mounting Hole Center:

5.200 inches

Angular Deviation Of First Hole From Top Center In Deg:

170.0

Angular Deviation Of Second Hole From First Hole In Deg:

170.0

Distance Between Inside Surfaces Of Hinge Bracket:

Between 7.281 inches and 7.332 inches

Distance Between Outside Surfaces Of Hinge Bracket:

Between 8.471 inches and 8.548 inches

Bottom Mounting Hole Diameter:

Between 0.453 inches and 0.469 inches

Maximum Rated Armature Speed In Rpm:

8000

Thread Series:

Unf

Thread Class:

3a

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.375 inches

Mounting Hole Thready Qty Per Inch (tpi):

16

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

16

Voltage In Volts:

28.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A14700