NSN 2925-00-203-8735

Spark Plug - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2925-00-203-8735

Body	Stv	٠ ما
DOUV	OLV.	ıe.

Electrically shielded, partial insulator, gasket seat

Dc Resistance Rating In Ohms:

1500.0

Reach Length:

Between 0.792 inches and 0.812 inches

Usage Design:

Aircraft engine

Width Across Flats:

Between 0.870 inches and 0.878 inches

Electrode Style:

Triple gap ground electrode

Thread Size And Series/type Designator And Location:

3/4-20 unef shielding err-100

Mean Effective Pressure Rating:

415.0 pounds per square inch

Seat Major Diameter:

Between 0.950 inches and 0.970 inches

Height Above Mounting Surface:

Between 2.438 inches and 2.562 inches

Top To Terminal Contact Distance:

Between 1.485 inches and 1.585 inches

Top To Shield Thread Distance:

Between 0.105 inches and 0.145 inches

Shield Thread Length:

Between 0.335 inches and 0.375 inches

Barrel Inside Diameter:

0.560 inches

Terminal Sleeve Inside Diameter:

Between 0.378 inches and 0.398 inches

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A10400