## NSN 2925-00-203-8735

Spark Plug - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2925-00-203-8735

<b>Body</b>	Stv	٠ ما
DOUV	OLV.	ıe.

Electrically shielded, partial insulator, gasket seat

Dc Resistance Rating In Ohms:

1500.0

Reach Length:

Between 0.792 inches and 0.812 inches

**Usage Design:** 

Aircraft engine

Width Across Flats:

Between 0.870 inches and 0.878 inches

**Electrode Style:** 

Triple gap ground electrode

Thread Size And Series/type Designator And Location:

3/4-20 unef shielding err-100

Mean Effective Pressure Rating:

415.0 pounds per square inch

**Seat Major Diameter:** 

Between 0.950 inches and 0.970 inches

**Height Above Mounting Surface:** 

Between 2.438 inches and 2.562 inches

**Top To Terminal Contact Distance:** 

Between 1.485 inches and 1.585 inches

**Top To Shield Thread Distance:** 

Between 0.105 inches and 0.145 inches

**Shield Thread Length:** 

Between 0.335 inches and 0.375 inches

**Barrel Inside Diameter:** 

0.560 inches

**Terminal Sleeve Inside Diameter:** 

Between 0.378 inches and 0.398 inches

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

Yes - demil/mli

Fiig:

A10400