

View Online at <https://aerobasegroup.com/nsn/2925-00-288-1394>

**Body Material:**

Aluminum

**Drive Connection Type:**

Impulse coupled

**Mounting Slot Width:**

Between 0.385 inches and 0.395 inches

**Mounting Slot Length:**

1.125 inches

**Distance Between Mounting Facility Centers:**

Between 4.182 inches and 4.194 inches

**Performance Type:**

High tension

**Drive Shaft Type:**

Threaded

**Shaft Rotation Direction:**

Counterclockwise

**Mounting Facility Quantity:**

2

**Pole Quantity:**

2

**Distributor Cap:**

Not included

**Mounting Method:**

Flange

**Impulse Quantity Per Revolution:**

6

**Ignition Type For Which Designed:**

Single

**Rotation Element Type:**

Permanent magnet rotor

**Contact Set Quantity:**

1

**Mounting Facility:**

Slot

**Features Provided:**

Radio interference shielding

**Spark Distribution Method:**

Gap

**Surface Treatment:**

Enamel

**Surface Treatment:**

Enamel

**Fsc Application Data:**

Engine electrical system, aircraft

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A12200