## NSN 2925-00-294-2596

Ignition Magneto - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2925-00-294-2596

| ····· -····                      |                |
|----------------------------------|----------------|
| Body Material:                   |                |
| Aluminum alloy                   |                |
| Drive Connection Type:           |                |
| Rigid coupled                    |                |
| Mounting Slot Width:             |                |
| 0.328 inches                     |                |
| Mounting Slot Length:            |                |
| 1.125 inches                     |                |
| Shaft Length:                    |                |
| 1.469 inches                     |                |
| Environmental Protection:        |                |
| Fungus resistant                 |                |
| Distance Between Mounting Fac    | ility Centers: |
| 6.000 inches                     |                |
| Performance Type:                |                |
| Low tension                      |                |
| Drive Shaft Type:                |                |
| Straight spline                  |                |
| Shaft Rotation Direction:        |                |
| Counterclockwise                 |                |
| Mounting Facility Quantity:      |                |
| 4                                |                |
| Pole Quantity:                   |                |
| 4                                |                |
| Mounting Method:                 |                |
| Flange                           |                |
| Ignition Type For Which Designed | ed:            |
| Dual                             |                |
| Rotation Element Type:           |                |
| Permanent magnet rotor           |                |
| Contact Set Quantity:            |                |
| 2                                |                |
| Mounting Facility:               |                |
| Slot                             |                |
| Features Provided:               |                |
| Radio interference shielding     |                |
| Spark Distribution Method:       |                |
| Contact                          |                |
| Surface Treatment:               |                |
| Enamel                           |                |
| Surface Treatment:               |                |
| Enamel                           |                |
|                                  |                |

## NSN 2925-00-294-2596

Ignition Magneto - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A12200

