Ignition System Distributor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2925-00-555-0584

Magnesium Drive Connection Type: Rigid scupiled Mounting Stot Witht: 0.391 inches Mounting Stot Length: 0.922 inches Shaft Length: 1.151 inches Environmental Protection: Fungus resistant Distance Between Mounting Facility Centers: 5.250 inches Drive Shaft Type: Threaded Mounting Facility Quantity: 3 Distance Detween Mounting Facility Centers: Clockwise Mounting Facility Quantity: 3 Distributor Cap: Not included Mounting Method: Base Impulse Quantity Per Revolution: 18 Primary Terminal Accommodation Type: Wire lead Spark Advance Control Method: Manual Maximum Advance Deg: 6.0 Contact Set Quantity: 4 Mounting Facility: Stot Factures Providet: Radio interference shielding	-
Prive Connection Type: Rigid coupled Mounting Slot Width: 0.321 inches Mounting Slot Length: 0.322 inches Shaft Length: 1.151 inches Environmental Protection: Fungus resistant Distance Between Mounting Facility Centers: 5.250 inches Drive Shaft Type: Threaded Shaft Cation Direction: Clockwise Mounting Facility Quantity: 3 Distifutor Cap: Not included Mounting Method: Base Inglition Type For Which Designed: Single Primary Terminal Accommodation Type: Wire lead Spark Advance Control Method: Annual Maximum Advance Deg: 5.0 Conct Set Quantity: 4 Mounting Facility: Slot Factures Provide: Radio interference shielding	Body Material:
Rigid coupled Mounting Slot Width: 0.391 inches Mounting Slot Length: 0.322 inches Shaft Length: 1.151 inches Environmental Protection: Fungus resistant Distance Between Mounting Facility Centers: 5.250 inches Drive Shaft Type: Threaded Shaft Cation Direction: Clockwise Mounting Method: Base Distince Dely contents: Sold Bott Reading Method: Base Impulse Quantity Per Revolution: 18 Ignition Type For Which Designed: Saya Sayal Manual Manual Maximum Advance Control Method: Sayal Sayal Cinct Set Quantity: Sayal Sayal Maximum Advance Deg: Sayal Sayal Cinct Set Quantity: Sayal Mounting Facility: Sayal Cinter Seronvide:<	
Nounting Slot Width:0.391 inchesMounting Slot Length:0.922 inchesShaft Length:1.151 inchesEnvironmental Protection:Fungus resistantDistance Between Mounting Facility Centers:5.250 inchesDrive Shaft Type:ThreadedShaft Rotation Direction:ClockwiseMounting Facility Canters:3Distince Between Mounting:3Bistince Cap:Not includedMounting Method:BaseInpulse Quantity Per Revolution:18Ignition Type For Which Designed:SinglePrimary Terminal Accommodation Type:Wire leadManualMaximum Advance Deg:5.0Conct Set Quantity:4Mounting Facility:SoltFactures Provided:Radio interference shielding	
0.391 inclusion0.392 inclusion0.392 inclusionShaft Length:1.151 inclusionEnvironmental Protection:Fungus resistantDistance Between Mounting Facility Centers:5.250 inclusion5.250 inclusionClockwiseMounting Facility Centers:ClockwiseMounting Facility Quantity:3Distributor Cap:Not includedMounting Method:BaseImpulse Quantity Per Revolution:18SinglePrimary Terminal Accommodation Type:Wire leadSanta Advance Control Method:5.0Control Sequencies5.1SoltMounting Facility:5.0Control Method:5.0Control Method:5.0SoltFactures Providei:SoltFactures Providei:Factures Providei: <th></th>	
Nounting Slot Length:0.922 linchesShaft Length:1.151 linchesEnvironmental Protection:Fungus resistantDistance Between Mounting Facility Centers:5.250 linchesDrive Shaft Type:ThreadedShaft Rotation Direction:ClockwiseMounting Facility Quantity:3Distributor Cap:Not includedMounting Method:BaseImpulse Quantity Per Revolution:18SinglePrimary Terminal Accommodation Type:Wire leadMaxiumAdvance Deg:5.0Contact Set Quantity:4Mounting Facility:StotFurnal Facility:StotFacility:StotFacility:StotFactures Provided:Factures Provided:Factures Provided:Factures Provided:Factures Provided:Factures Provided:Factures Provided:Factures Provided:Factures Provided:Factures Provide:Factures P	
0.922 inches Shaft Length: 1.151 inches Environmental Protection: Fungus resistant Distance Between Mounting Facility Centers: 5.260 inches Drive Shaft Type: Threade Shaft Rotation Direction: Clockwise Mounting Facility Quantity: 3 Distributor Cap: Not included Mounting Method: Base Inpulse Quantity Per Revolution: 18 Ignition Type For Which Designed: Single Primary Terminal Accommodation Type: Wire lad Shart Advance Deg: 5.0 Contact Set Quantity: 4 Mounting Facility: Stot Factures Provided: Radio interference shielding	
Shaft Length:1.151 inchesEnvironmental Protection:Fungus resistantDistance Between Mounting Facility Centers:5.250 inchesDrive Shaft Type:ThreadedShaft Rotation Direction:ClockwiseMounting Facility Quantity:3Distributor Cap:Not includedMounting Method:BaseInpulse Quantity Per Revolution:18Ignition Type For Which Designed:SinglePrimary Terminal Accommodation Type:Wire leadManualMaximum Advance Deg:6.0Contact Set Quantity:4Mounting Facility:StotFeatures Provided:Ratio interference shielding	
1.151 inches Environmental Protection: Fungus resistant Distance Between Mounting Facility Centers: 5.250 inches Drive Shaft Type: Threaded Shaft Rotation Direction: Clockwise Mounting Facility Quantity: 3 Distributor Cap: Not included Mounting Method: Base Impulse Quantity Per Revolution: 18 Ignition Type For Which Designed: Single Primary Terminal Accommodation Type: Wire lead Spark Advance Control Method: 5.0 Contact Set Quantity: 4 Mounting Facility: Stot Factures Provided: Radio interference shielding	0.922 inches
Evrironmental Protection: Fungus resistant Distance Between Mounting Facility Centers: 5.250 inches Drive Shaft Type: Threaded Shaft Rotation Direction: Clockwise Mounting Facility Quantity: 3 Distributor Cap: Not included Mounting Method: Base Inguise Quantity Per Revolution: 18 Ignition Type For Which Designed: Single Primary Terminal Accommodation Type: Wire lead Spark Advance Control Method: 5.0 Contact Set Quantity: 4 Mounting Facility: Stot Factures Provided:	Shaft Length:
Fungus resistant Distance Between Mounting Facility Centers: 5.250 inches Drive Shaft Type: Threaded Shaft Rotation Direction: Clockwise Mounting Facility Quantity: 3 Distributor Cap: Not included Mounting Method: Base Impulse Quantity Per Revolution: 18 Primary Terminal Accommodation Type: Vire lead Spark Advance Control Method: Annual Maximum Advance Deg: 5.0 Contact Set Quantity: Stor Fatures Provided: Rounting Facility: Stor Factures Provided:	1.151 inches
Distance Between Mounting Facility Centers:5.250 inchesDrive Shaft Type:ThreadedShaft Rotation Direction:ClockwiseMounting Facility Quantity:3Distributor Cap:Not includedMounting Method:BaseInpulse Quantity Per Revolution:18Ignition Type For Which Designed:SinglePrimary Terminal Accommodation Type:Wire leadSpark Advance Control Method:5.0Contact Set Quantity:4Mounting Facility:StotFacures Provided:Roto interference shielding	Environmental Protection:
5.250 inchesDrive Shaft Type:ThreadedShaft Rotation Direction:ClockwiseMounting Facility Quantity:3Distributor Cap:Not includedMounting Method:BaseImpulse Quantity Per Revolution:18Ignition Type For Which Designed:SinglePrimary Terminal Accommodation Type:Wire leadBanualManualManualMaximum Advance Deg:5.0Contact Set Quantity:4Mounting Facility:StotFacures Provided:Radio interference shielding	Fungus resistant
Prive Shaft Type:ThreadedShaft Rotation Direction:ClockwiseMounting Facility Quantity:3Distributor Cap:Not includedMounting Method:BaseImpulse Quantity Per Revolution:18Ignition Type For Which Designed:SinglePrimary Terminal Accommodation Type:Wire leadManualManualContact Set Quantity:4Mounting Facility:StotFourtien For Which Designed:StotPrimary Terminal Accommodation Type:StotPrimary Revolution:5.0Contact Set Quantity:5.0Faures Provided:StotFaures Provided:Radio interference shielding	Distance Between Mounting Facility Centers:
ThreadedShaft Rotation Direction:ClockwiseMounting Facility Quantity:3Distributor Cap:Not includedMounting Method:BaseImpulse Quantity Per Revolution:18Ignition Type For Which Designed:SinglePrimary Terminal Accommodation Type:Wire leadSpark Advance Control Method:5.0Contact Set Quantity:4Mounting Facility:StotFatures Provided:Radio interference shielding	5.250 inches
Shaft Rotation Direction:ClockwiseMounting Facility Quantity:3Distributor Cap:Not includedMounting Method:BaseImpulse Quantity Per Revolution:18Ignition Type For Which Designed:SinglePrimary Terminal Accommodation Type:Wire leadSpark Advance Control Method:5.0Contact Set Quantity:4Mounting Facility:StotFatures Provided:Radio interference shielding	Drive Shaft Type:
ClockwiseMounting Facility Quantity:3Distributor Cap:Not includedMounting Method:BaseImpulse Quantity Per Revolution:18Ignition Type For Which Designed:SinglePrimary Terminal Accommodation Type:Wire leadSpark Advance Control Method:AnnualManualMaximum Advance Deg:5.0Contact Set Quantity:4Mounting Facility:StotFactures Provided:Radio interference shielding	Threaded
Mounting Facility Quantity:3Jostributor Cap:Not includedMounting Method:BaseImpulse Quantity Per Revolution:18Ignition Type For Which Designed:SinglePrimary Terminal Accommodation Type:Wire leadSpark Advance Control Method:5.0Contact Set Quantity:4Mounting Facility:StotFeatures Provided:Radio interference shielding	Shaft Rotation Direction:
3 Distributor Cap: Not included Mounting Method: Base Impulse Quantity Per Revolution: 18 Ignition Type For Which Designed: Single Primary Terminal Accommodation Type: Wire lead Spark Advance Control Method: Manual Maximum Advance Deg: 5.0 Contact Set Quantity: 4 Mounting Facility: Slot Factures Provided: Radio interference shielding	Clockwise
Distributor Cap:Not includedMounting Method:BaseImpulse Quantity Per Revolution:18Ignition Type For Which Designed:SinglePrimary Terminal Accommodation Type:Wire leadSpark Advance Control Method:ManualMaximum Advance Deg:5.0Contact Set Quantity:4StotFeatures Provided:Radio interference shielding	Mounting Facility Quantity:
Not includedMounting Method:BaseImpulse Quantity Per Revolution:18Ignition Type For Which Designed:SinglePrimary Terminal Accommodation Type:Wire leadSpark Advance Control Method:ManualMaximum Advance Deg:5.0Contact Set Quantity:4SlotFeatures Provided:Radio interference shielding	3
Mounting Method:BaseImpulse Quantity Per Revolution:18Ignition Type For Which Designed:SinglePrimary Terminal Accommodation Type:Wire leadSpark Advance Control Method:ManualMaximum Advance Deg:5.0Contact Set Quantity:4Mounting Facility:SlotFeatures Provided:Radio interference shielding	Distributor Cap:
Base Impulse Quantity Per Revolution: 18 Ignition Type For Which Designed: Single Primary Terminal Accommodation Type: Wire lead Spark Advance Control Method: Manual Maximum Advance Deg: 5.0 Contact Set Quantity: 4 Mounting Facility: Slot Features Provided: Radio interference shielding	Not included
Impulse Quantity Per Revolution:18Ignition Type For Which Designed:SinglePrimary Terminal Accommodation Type:Wire leadSpark Advance Control Method:ManualMaximum Advance Deg:5.0Contact Set Quantity:4Mounting Facility:SlotFeatures Provided:Radio interference shielding	Mounting Method:
18 Ignition Type For Which Designed: Single Primary Terminal Accommodation Type: Wire lead Spark Advance Control Method: Manual Maximum Advance Deg: 5.0 Contact Set Quantity: 4 Mounting Facility: Slot Features Provided: Radio interference shielding	Base
18 Ignition Type For Which Designed: Single Primary Terminal Accommodation Type: Wire lead Spark Advance Control Method: Manual Maximum Advance Deg: 5.0 Contact Set Quantity: 4 Mounting Facility: Slot Features Provided: Radio interference shielding	Impulse Quantity Per Revolution:
Single Primary Terminal Accommodation Type: Wire lead Spark Advance Control Method: Manual Maximum Advance Deg: 5.0 Contact Set Quantity: 4 Mounting Facility: Slot Features Provided: Radio interference shielding	
Primary Terminal Accommodation Type:Wire leadSpark Advance Control Method:ManualMaximum Advance Deg:5.0Contact Set Quantity:4Mounting Facility:SlotFeatures Provided:Radio interference shielding	Ignition Type For Which Designed:
Primary Terminal Accommodation Type:Wire leadSpark Advance Control Method:ManualMaximum Advance Deg:5.0Contact Set Quantity:4Mounting Facility:SlotFeatures Provided:Radio interference shielding	Single
Wire leadSpark Advance Control Method:ManualMaximum Advance Deg:5.0Contact Set Quantity:4Mounting Facility:SlotFeatures Provided:Radio interference shielding	
Spark Advance Control Method:ManualMaximum Advance Deg:5.0Contact Set Quantity:4Mounting Facility:SlotFeatures Provided:Radio interference shielding	
Manual Maximum Advance Deg: 5.0 Contact Set Quantity: 4 Mounting Facility: Slot Features Provided: Radio interference shielding	
Maximum Advance Deg:5.0Contact Set Quantity:4Mounting Facility:SlotFeatures Provided:Radio interference shielding	
5.0 Contact Set Quantity: 4 Mounting Facility: Slot Features Provided: Radio interference shielding	
Contact Set Quantity: 4 Mounting Facility: Slot Features Provided: Radio interference shielding	
4 Mounting Facility: Slot Features Provided: Radio interference shielding	
Mounting Facility: Slot Features Provided: Radio interference shielding	
Slot Features Provided: Radio interference shielding	
Features Provided: Radio interference shielding	
Radio interference shielding	
	Spark Distribution Method:
Contact	

NSN 2925-00-555-0584

Ignition System Distributor - Page 2 of 2



Special Features:

Surface treatment black enamel

Surface Treatment:

Enamel

Surface Treatment:

Enamel

Fsc Application Data:

Engine electrical system, aircraft

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A12200