## NSN 2925-00-640-7224

Spark Plug - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2925-00-640-7224

view Online at https://aerobasegroup.com/nsn/2925-00-640
Body Style:
Electrically shielded, partial insulator, gasket seat
Dc Resistance Rating In Ohms:
1000.0
Reach Length:
Between 0.792 inches and 0.812 inches
Usage Design:
Aircraft engine
Width Across Flats:
Between 0.870 inches and 0.878 inches
Electrode Style:
Triple gap ground electrode
Thread Size And Series/type Designator And Location:
5/8-24 unef shielding
Mean Effective Pressure Rating:
340.0 pounds per square inch
Seat Major Diameter:
Between 0.865 inches and 0.970 inches
Height Above Mounting Surface:
2.250 inches
Top To Terminal Contact Distance:
1.000 inches
Top To Shield Thread Distance:
0.125 inches
Shield Thread Length:
0.375 inches
Barrel Inside Diameter:
Between 0.559 inches and 0.560 inches
Terminal Sleeve Inside Diameter:
Between 0.378 inches and 0.388 inches
Shelf Life:
N/a

**Unit Of Measure:** 

**Demilitarization:** Yes - demil/mli

**Fiig:** A10400