NSN 2925-00-640-7827

Spark Plug - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2925-00-640-7827

D			Stv	.1	_	
D	ou	IV	ÐΙ	/	е	

Electrically shielded, partial insulator, gasket seat

Dc Resistance Rating In Ohms:

1000.0

Reach Length:

Between 0.792 inches and 0.812 inches

Usage Design:

Engine other than aircraft

Width Across Flats:

Between 0.872 inches and 0.878 inches

Electrode Style:

Four gap ground electrode

Thread Size And Series/type Designator And Location:

3/4-20 unef shielding err-100

Mean Effective Pressure Rating:

300.0 pounds per square inch

Seat Major Diameter:

0.970 inches

Height Above Mounting Surface:

Between 2.469 inches and 2.531 inches

Top To Terminal Contact Distance:

1.500 inches

Top To Shield Thread Distance:

Between 0.105 inches and 0.145 inches

Shield Thread Length:

Between 0.335 inches and 0.375 inches

Barrel Inside Diameter:

Between 0.378 inches and 0.386 inches

Terminal Sleeve Inside Diameter:

0.290 inches

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A10400