## NSN 2940-01-159-6200

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2940-01-159-6200

Mounting Type:
Threaded hole top
Mounting Hole Quantity:
4
Body Outside Diameter:
4.570 inches
Body Height:
9.250 inches
Filtration Rating In Microns:
12.0 absolute
Differential Pressure:
25.0 pounds per square inch
Distance Between Mounting Hole Centers:
2.500 inches and 2.502 inches
Design Type:
Reusable
Tempurature Rating:
Between -45.0 degrees fahrenheit and 275.0 degrees fahrenheit
Features Provided:
Air bleed valve and antidrain back device and by-pass valve and differential pressure indicator and thermal lockout
Filtering Element Quantity:
1
Mounting Facility Thread Series Designator:
Unc
Maximum Operating Pressure:
1000.0 pounds per square inch
Filtering Media Design:
Pleated single filtering media response
First Intake Connection Type:
Threaded internal tube head side
Mounting Facility Thread Size:
0.315 inches
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Thread Series Designator:
Un
First Intake Thread Size:
1.0625 inches
First Intake Thready Qty Per Inch (tpi):
12

3b

First Intake Thread Class:

## **NSN 2940-01-159-6200** Fluid Filter - Page 2 of 2



First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Special Features:
Low pressure; knurled gripping band
Material:
Steel sediment bowl or stainless steel sediment bowl
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
High pressure threaded body
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A24000