# NSN 2940-01-159-6200

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2940-01-159-6200

# Mounting Type:

Threaded hole top

# Mounting Hole Quantity:

4

## Body Outside Diameter:

4.570 inches

### **Body Height:**

9.250 inches

#### **Filtration Rating In Microns:**

12.0 absolute

### **Differential Pressure:**

25.0 pounds per square inch

### **Distance Between Mounting Hole Centers:**

2.500 inches and 2.502 inches

#### Design Type:

Reusable

#### **Tempurature Rating:**

Between -45.0 degrees fahrenheit and 275.0 degrees fahrenheit

### Features Provided:

Air bleed valve and antidrain back device and by-pass valve and differential pressure indicator and thermal lockout

## **Filtering Element Quantity:**

1

# Mounting Facility Thread Series Designator:

Unc

### Maximum Operating Pressure:

1000.0 pounds per square inch

#### Filtering Media Design:

Pleated single filtering media response

### First Intake Connection Type:

Threaded internal tube head side

### Mounting Facility Thread Size:

0.315 inches

### First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

### First Intake Thread Series Designator:

Un

First Intake Thread Size:

1.0625 inches

# First Intake Thready Qty Per Inch (tpi):

12

First Intake Thread Class:

3b

# NSN 2940-01-159-6200

Fluid Filter - Page 2 of 2

---



**First Intake Thread Direction: Right-hand** Filtering System For Which Designed: Full flow **Special Features:** Low pressure; knurled gripping band Material: Steel sediment bowl or stainless steel sediment bowl Media For Which Designed: Fuel/oil, hydrocarbon Style Designator: High pressure threaded body Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A24000