

View Online at <https://aerobasegroup.com/nsn/2940-01-330-2521>

**Mounting Type:**

Threaded hole top side

**Mounting Hole Quantity:**

2

**Body Length:**

5.500 inches

**Body Width:**

5.000 inches

**Body Height:**

11.420 inches

**Filtration Rating In Microns:**

25.0

**Drop Pressure:**

16.5 pounds per square inch

**Distance Between Mounting Hole Centers:**

1.880 inches

**End Application:**

Truck, firefighting, structural, model 1000gpm, type a/s p22/p24

**Design Type:**

Reusable

**Temperature Rating:**

Between 20.0 degrees fahrenheit and 300.0 degrees fahrenheit

**Features Provided:**

By-pass valve

**Filtering Element Quantity:**

1

**Mounting Facility Thread Series Designator:**

Unc

**Maximum Operating Pressure:**

200.0 pounds per square inch

**Filtering Media Design:**

Pleated single filtering media response

**First Intake Connection Type:**

Threaded internal pipe head side

**Mounting Facility Thread Size:**

0.312 inches

**First Discharge Connection Relationship To Intake Connection:**

Identical to first intake connection

**Distance From Bottom Of Body To Center Of Inlet:**

10.030 inches

**First Intake Thread Series Designator:**

Nptf

**First Intake Thread Size:**

1.250 inches

**First Intake Thread Direction:**

Right-hand

**Filtering System For Which Designed:**

Full flow

**Special Features:**

Spin-on type element; filter drilled at all four locations for pressure gauge

**Material:**

Paper filtering medium

**Media For Which Designed:**

Fuel/oil, hydrocarbon

**Style Designator:**

Tee type (hydraulic)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A24000