

View Online at <https://aerobasegroup.com/nsn/2940-01-330-2521>

Mounting Type:

Threaded hole top side

Mounting Hole Quantity:

2

Body Length:

5.500 inches

Body Width:

5.000 inches

Body Height:

11.420 inches

Filtration Rating In Microns:

25.0

Drop Pressure:

16.5 pounds per square inch

Distance Between Mounting Hole Centers:

1.880 inches

End Application:

Truck, firefighting, structural, model 1000gpm, type a/s p22/p24

Design Type:

Reusable

Temperature Rating:

Between 20.0 degrees fahrenheit and 300.0 degrees fahrenheit

Features Provided:

By-pass valve

Filtering Element Quantity:

1

Mounting Facility Thread Series Designator:

Unc

Maximum Operating Pressure:

200.0 pounds per square inch

Filtering Media Design:

Pleated single filtering media response

First Intake Connection Type:

Threaded internal pipe head side

Mounting Facility Thread Size:

0.312 inches

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

Distance From Bottom Of Body To Center Of Inlet:

10.030 inches

First Intake Thread Series Designator:

Nptf

First Intake Thread Size:

1.250 inches

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

Special Features:

Spin-on type element; filter drilled at all four locations for pressure gauge

Material:

Paper filtering medium

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

Tee type (hydraulic)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A24000