## NSN 2940-01-432-3894

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2940-01-432-3894

**Mounting Type:** Outlet connection top **Body Outside Diameter:** 7.000 inches **Body Height:** 23.870 inches **Drop Pressure:** 50.0 pounds per square inch **Differential Pressure:** 50.0 pounds per square inch **End Application:** 2350-01-081-8123 **Design Type:** Reusable **Features Provided:** By-pass valve and differential pressure indicator **Filtering Element Quantity:** 1 **Maximum Operating Pressure:** 300.0 pounds per square inch **First Intake Connection Type:** Threaded internal tube top side First Discharge Connection Relationship To Intake Connection: Not identical **First Discharge Connection Type:** Threaded internal tube head side First Intake Thread Series Designator: Unf First Discharge Thread Series Designator: Un First Intake Thread Size: 0.875 inches First Discharge Thread Size: 1.312 inches First Discharge Thready Qty Per Inch (tpi): 12 First Intake Thread Class: 2b First Discharge Thread Class:

**First Intake Thread Direction:** 

Right-hand

## NSN 2940-01-432-3894

Fluid Filter - Page 2 of 2



First Discharge Thread Direction:
Right-hand
Filtering System For Which Designed:
By-pass flow
Material:
Steel body
Media For Which Designed:
Fuel/oil, hydrocarbon
Surface Treatment:
Paint body
Style Designator:
Ell type (hydraulic)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A24000