

View Online at <https://aerobasegroup.com/nsn/2940-01-432-3894>

Mounting Type:

Outlet connection top

Body Outside Diameter:

7.000 inches

Body Height:

23.870 inches

Drop Pressure:

50.0 pounds per square inch

Differential Pressure:

50.0 pounds per square inch

End Application:

2350-01-081-8123

Design Type:

Reusable

Features Provided:

By-pass valve and differential pressure indicator

Filtering Element Quantity:

1

Maximum Operating Pressure:

300.0 pounds per square inch

First Intake Connection Type:

Threaded internal tube top side

First Discharge Connection Relationship To Intake Connection:

Not identical

First Discharge Connection Type:

Threaded internal tube head side

First Intake Thread Series Designator:

Unf

First Discharge Thread Series Designator:

Un

First Intake Thread Size:

0.875 inches

First Discharge Thread Size:

1.312 inches

First Discharge Thread Qty Per Inch (tpi):

12

First Intake Thread Class:

2b

First Discharge Thread Class:

28

First Intake Thread Direction:

Right-hand

First Discharge Thread Direction:

Right-hand

Filtering System For Which Designed:

By-pass flow

Material:

Steel body

Media For Which Designed:

Fuel/oil, hydrocarbon

Surface Treatment:

Paint body

Style Designator:

EII type (hydraulic)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000