NSN 2940-01-497-5039

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2940-01-497-5039

Mounting Type:

Unthreaded hole top side

Mounting Hole Diameter:

0.345 inches

Mounting Hole Quantity:

2

Body Outside Diameter:

3.750 inches

Body Height:

7.850 inches

Filtration Rating In Microns:

0.6 absolute

Drop Pressure:

1.0 pounds per square inch

Distance Between Mounting Hole Centers:

2.000 inches

End Application:

Aircraft support equipment test console, b-2 bomber.

Design Type:

Reusable

Tempurature Rating:

Between -40.0 degrees fahrenheit and 250.0 degrees fahrenheit

Filtering Element Quantity:

1

Maximum Operating Pressure:

5000.0 pounds per square inch

First Intake Connection Type:

Threaded internal pipe head

Second Intake Connection Relationship To First Intake Connection:

Identical

First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

First Intake Thread Series Designator:

Npt

First Intake Thread Size:

0.750 inches

Product Name:

Filter unit

First Intake Thread Direction:

Right-hand

Filtering System For Which Designed:

Full flow

NSN 2940-01-497-5039

Fluid Filter - Page 2 of 2



Special Features:

Filter designed to remove water particles only from a gaseous media; pressure ratings, proof 7, 500 psi, burst 20, 000 psi; mrc askq is for o-ring temp; element temp range m70.0 fah - 300.0 fah; element constructed of glass epoxy, carbon steel, and stainless steel; 80-1500 cfm; replacement element p/n u-345.

Material:

Aluminum alloy 2024 body

Media For Which Designed:

Gas

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A24000