NSN 2940-01-517-5733

Fluid Filter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2940-01-517-5733

Design Type: Reusable Tempurature Rating: Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit Filtering Element Quantity: 1 Maximum Operating Pressure: 6000.0 pounds per square inch Product Name: Filter assembly Special Features: Flows: 150gpm; fatigue pressure rating: 3000psi; burst pressure: 20,000psi; nitrile seals; ports: flange sae j518c-code 61; full flow response bypass valve: 50psid; differential pressure device: electrical switch (spdt) w/6in. Leads; bleed port and plug; multiple port options; ductile iron head; forged steel bowl; ultipor iii element; drain port and plug Material: Rubber synthetic seal Style Designator: Straight flow basket strainer w/ bolted cover Shelf Life: N/a Unit Of Measure: Demilitarization:	
Tempurature Rating: Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit Filtering Element Quantity: 1 Maximum Operating Pressure: 6000.0 pounds per square inch Product Name: Filter assembly Special Features: Flows: 150gpm; fatigue pressure rating: 3000psi; burst pressure: 20, 000psi; nitrile seals; ports: flange sae j518c-code 61; full flow response bypass valve: 50psid; differential pressure device: electrical switch (spdt) w/6in. Leads; bleed port and plug; multiple port options; ductile iron head; forged steel bowl; ultipor iii element; drain port and plug Material: Rubber synthetic seal Style Designator: Straight flow basket strainer w/ bolted cover Shelf Life: N/a Unit Of Measure:	n Type:
Between -45.0 degrees fahrenheit and 225.0 degrees fahrenheit Filtering Element Quantity: 1 Maximum Operating Pressure: 6000.0 pounds per square inch Product Name: Filter assembly Special Features: Flows: 150gpm; fatigue pressure rating: 3000psi; burst pressure: 20, 000psi; nitrile seals; ports: flange sae j518c-code 61; full flow response bypass valve: 50psid; differential pressure device: electrical switch (spdt) w/6in. Leads; bleed port and plug; multiple port options; ductile iron head; forged steel bowl; ultipor iii element; drain port and plug Material: Rubber synthetic seal Style Designator: Straight flow basket strainer w/ bolted cover Shelf Life: N/a Unit Of Measure:	ble
Filtering Element Quantity: 1 Maximum Operating Pressure: 6000.0 pounds per square inch Product Name: Filter assembly Special Features: Flows: 150gpm; fatigue pressure rating: 3000psi; burst pressure: 20, 000psi; nitrile seals; ports: flange sae j518c-code 61; full flow response bypass valve: 50psid; differential pressure device: electrical switch (spdt) w/6in. Leads; bleed port and plug; multiple port options; ductile iron head; forged steel bowl; ultipor iii element; drain port and plug Material: Rubber synthetic seal Style Designator: Straight flow basket strainer w/ bolted cover Shelf Life: N/a Unit Of Measure:	urature Rating:
Maximum Operating Pressure: 6000.0 pounds per square inch Product Name: Filter assembly Special Features: Flows: 150gpm; fatigue pressure rating: 3000psi; burst pressure: 20, 000psi; nitrile seals; ports: flange sae j518c-code 61; full flow response bypass valve: 50psid; differential pressure device: electrical switch (spdt) w/6in. Leads; bleed port and plug; multiple port options; ductile iron head; forged steel bowl; ultipor iii element; drain port and plug Material: Rubber synthetic seal Style Designator: Straight flow basket strainer w/ bolted cover Shelf Life: N/a Unit Of Measure:	en -45.0 degrees fahrenheit and 225.0 degrees fahrenheit
Maximum Operating Pressure: 6000.0 pounds per square inch Product Name: Filter assembly Special Features: Flows: 150gpm; fatigue pressure rating: 3000psi; burst pressure: 20, 000psi; nitrile seals; ports: flange sae j518c-code 61; full flow response bypass valve: 50psid; differential pressure device: electrical switch (spdt) w/6in. Leads; bleed port and plug; multiple port options; ductile iron head; forged steel bowl; ultipor iii element; drain port and plug Material: Rubber synthetic seal Style Designator: Straight flow basket strainer w/ bolted cover Shelf Life: N/a Unit Of Measure:	ng Element Quantity:
6000.0 pounds per square inch Product Name: Filter assembly Special Features: Flows: 150gpm; fatigue pressure rating: 3000psi; burst pressure: 20, 000psi; nitrile seals; ports: flange sae j518c-code 61; full flow response bypass valve: 50psid; differential pressure device: electrical switch (spdt) w/6in. Leads; bleed port and plug; multiple port options; ductile iron head; forged steel bowl; ultipor iii element; drain port and plug Material: Rubber synthetic seal Style Designator: Straight flow basket strainer w/ bolted cover Shelf Life: N/a Unit Of Measure:	
Product Name: Filter assembly Special Features: Flows: 150gpm; fatigue pressure rating: 3000psi; burst pressure: 20, 000psi; nitrile seals; ports: flange sae j518c-code 61; full flow response bypass valve: 50psid; differential pressure device: electrical switch (spdt) w/6in. Leads; bleed port and plug; multiple port options; ductile iron head; forged steel bowl; ultipor iii element; drain port and plug Material: Rubber synthetic seal Style Designator: Straight flow basket strainer w/ bolted cover Shelf Life: N/a Unit Of Measure:	num Operating Pressure:
Filter assembly Special Features: Flows: 150gpm; fatigue pressure rating: 3000psi; burst pressure: 20, 000psi; nitrile seals; ports: flange sae j518c-code 61; full flow response bypass valve: 50psid; differential pressure device: electrical switch (spdt) w/6in. Leads; bleed port and plug; multiple port options; ductile iron head; forged steel bowl; ultipor iii element; drain port and plug Material: Rubber synthetic seal Style Designator: Straight flow basket strainer w/ bolted cover Shelf Life: N/a Unit Of Measure:) pounds per square inch
Special Features: Flows: 150gpm; fatigue pressure rating: 3000psi; burst pressure: 20, 000psi; nitrile seals; ports: flange sae j518c-code 61; full flow response bypass valve: 50psid; differential pressure device: electrical switch (spdt) w/6in. Leads; bleed port and plug; multiple port options; ductile iron head; forged steel bowl; ultipor iii element; drain port and plug Material: Rubber synthetic seal Style Designator: Straight flow basket strainer w/ bolted cover Shelf Life: N/a Unit Of Measure:	ct Name:
Flows: 150gpm; fatigue pressure rating: 3000psi; burst pressure: 20, 000psi; nitrile seals; ports: flange sae j518c-code 61; full flow response bypass valve: 50psid; differential pressure device: electrical switch (spdt) w/6in. Leads; bleed port and plug; multiple port options; ductile iron head; forged steel bowl; ultipor iii element; drain port and plug Material: Rubber synthetic seal Style Designator: Straight flow basket strainer w/ bolted cover Shelf Life: N/a Unit Of Measure:	assembly
response bypass valve: 50psid; differential pressure device: electrical switch (spdt) w/6in. Leads; bleed port and plug; multiple port options; ductile iron head; forged steel bowl; ultipor iii element; drain port and plug Material: Rubber synthetic seal Style Designator: Straight flow basket strainer w/ bolted cover Shelf Life: N/a Unit Of Measure:	al Features:
options; ductile iron head; forged steel bowl; ultipor iii element; drain port and plug Material: Rubber synthetic seal Style Designator: Straight flow basket strainer w/ bolted cover Shelf Life: N/a Unit Of Measure:	150gpm; fatigue pressure rating: 3000psi; burst pressure: 20, 000psi; nitrile seals; ports: flange sae j518c-code 61; full flow fas
Material: Rubber synthetic seal Style Designator: Straight flow basket strainer w/ bolted cover Shelf Life: N/a Unit Of Measure:	nse bypass valve: 50psid; differential pressure device: electrical switch (spdt) w/6in. Leads; bleed port and plug; multiple port
Rubber synthetic seal Style Designator: Straight flow basket strainer w/ bolted cover Shelf Life: N/a Unit Of Measure:	s; ductile iron head; forged steel bowl; ultipor iii element; drain port and plug
Style Designator: Straight flow basket strainer w/ bolted cover Shelf Life: N/a Unit Of Measure:	ial:
Straight flow basket strainer w/ bolted cover Shelf Life: N/a Unit Of Measure:	er synthetic seal
Shelf Life: N/a Unit Of Measure:	Designator:
N/a Unit Of Measure:	nt flow basket strainer w/ bolted cover
Unit Of Measure:	Life:
Demilitarization:	of Measure:
Demilitarization:	
	itarization:
No	
Fiig:	
A24000	0