

View Online at <https://aerobasegroup.com/nsn/2990-00-888-2856>

General Description:

A steel shaft, aisi c1117 or c1118, 5.76 in.Min, 5.79 in.Max o/a lg, 1st end 0.385 in.Min, 0.387 in.Max dia, 3.005 in.Min, 3.020 in.Max lg, grooved, 0.040 in.Min, 0.043 in.Max w of groove, 0.343 in.Min, 0.348 in.Max diameter of groove, 0.347 in.Min, 0.368 in.Max lg from end to groove, 1st step 0.435 in.Min, 0.436 in.Max dia, 0.160 in.Lg, 2nd end 1.210 in.Min, 1.250 in.Max lg, 0.498 in.Min, 0.500 in.Max dia, end slotted, 0.070 in.Min, 0.074 in.Max w of slot, 0.209 in.Dia drill, 1 in.Deep, 1st step, 2nd end, 0.410 in.Lg, 0.6691 in.Min, 0.6696 in.Max dia, groove between 2nd step and largest dia, 0.060 in.W, 0.650 in.Min, 0.660 in.Max diameter of groove, largest diameter 0.750 in, 0.900 in.Min, 0.905 in.Max lg, 0.850 in.Min, 0.880 in.Max lg of slot 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No