

View Online at https://aerobasegroup.com/nsn/2995-00-567-8912

| Dody Motorial |
|--|
| Body Material: |
| Steel |
| First End Outside Diameter: |
| Between 0.670 inches and 0.680 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit |
| Overall Height: |
| 3.538 inches |
| Body Outside Diameter: |
| 3.360 inches |
| Seat Angle In Deg: |
| 37.0 |
| First End External Thread Length: |
| Between 2.641 inches and 2.672 inches |
| Extended Length: |
| 26.820 inches |
| Integral Valve Operation Method: |
| Hydraulic |
| Design Characteristics: |
| Double acting single cylinder |
| First Piston Rod End Style: |
| External threaded |
| First Piston Rod End Thread Series Designator: |
| Unjf |
| First Piston Rod End Thread Diameter: |
| 0.750 inches |
| First Piston Rod End Thready Qty Per Inch (tpi): |
| 16 |
| First Piston Rod End Thread Class: |
| 3a |
| First Piston Rod End Thread Direction: |
| Left-hand |
| Port Location And Quantity: |
| 4 cylinder head end |
| Port Style: |
| Flared |
| Port Thread Series Designator: |
| Unjf |
| Port Thread Diameter: |
| 0.4375 inches |
| Port Thready Qty Per Inch (tpi): |
| 20 |
| |



Port Thread Class:

3a

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A34200