NSN 3010-00-025-7299

Shaft Coupling Half - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3010-00-025-7299

| Body Style: |
|--|
| Flexible pin |
| Overall Length: |
| 0.375 inches |
| Bore Diameter: |
| 0.2500 inches |
| Bore Length: |
| 0.3750 inches |
| Bore Shape: |
| Straight |
| Special Features: |
| Surface treatment: anodized; positioning facility bolt circle dia.: 1.250" nom.; positioning facility qty: 1; hole thread size designator: no. |
| (0.112") -40; unthreaded hole location: 90 deg. From threaded hole; unthreaded hole qty: 1; threaded hole location: on portion of hub 1/8" |
| from face; threaded hole qty: 1; securing method: threaded and or unthreaded hole; bore counterbore feature: not included; keying facility: |
| not included; o/a outside dimension: 1.625" nom.; hub od: 1/2" nom.; pin lg.: 0.250" nom.; thread provision: unthreaded; pin dia.: 0.540" |
| nom.; flange thickness: 0.125" nom.; hole dia.: 0.046" nom. |
| Material: |
| Aluminum |
| Material Specification: |
| Sae, 308 assn standard single material response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A521x0 |
| |
| |