

View Online at <https://aerobasegroup.com/nsn/3010-00-049-8782>

**Body Style:**

Flexible key insert type, partial bore

**Overall Length:**

0.438 inches

**Bore Diameter:**

0.2500 inches

**Bore Length:**

0.4380 inches

**Bore Shape:**

Straight

**Special Features:**

Fsc application data: oscillator, radio frequency, radio, except radio navigation, except airborne; surface treatment: cadmium plated; body keying facility depth/ht: 0.125" nom.; body keying facility wd: 0.236" nom.; hole thread size designator: 6-32; threaded hole location: centered 0.109" from end of hub and spaced 90 deg. Apart; threaded hole qty: 2; securing method: threaded hole; bore counterbore feature: included; keying facility type: integral key; keying facility spacing in deg.: 180.0; keying facility qty: 2; keying facility: included; counterbore location: coupling end; o/a outside dimension: 1" nom.; hub od: 1/2" nom.; thread provision: unthreaded; distance from center of bore to top of key: 0.0935" nom.; key wd: 0.236" nom.; flange thickness: 0.188" nom.; counterbore depth: 0.125" nom.; counterbore dia.: 0.313" nom.

**Material:**

Copper alloy

**Material Specification:**

Mil-b-895, ships amend i, condition 1/2 hard military specification single material response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A521x0

**Mil-std (military Standard):**

Mil-b-895 spec.