

View Online at <https://aerobasegroup.com/nsn/3010-00-049-8782>

Body Style:

Flexible key insert type, partial bore

Overall Length:

0.438 inches

Bore Diameter:

0.2500 inches

Bore Length:

0.4380 inches

Bore Shape:

Straight

Special Features:

Fsc application data: oscillator, radio frequency, radio, except radio navigation, except airborne; surface treatment: cadmium plated; body keying facility depth/ht: 0.125" nom.; body keying facility wd: 0.236" nom.; hole thread size designator: 6-32; threaded hole location: centered 0.109" from end of hub and spaced 90 deg. Apart; threaded hole qty: 2; securing method: threaded hole; bore counterbore feature: included; keying facility type: integral key; keying facility spacing in deg.: 180.0; keying facility qty: 2; keying facility: included; counterbore location: coupling end; o/a outside dimension: 1" nom.; hub od: 1/2" nom.; thread provision: unthreaded; distance from center of bore to top of key: 0.0935" nom.; key wd: 0.236" nom.; flange thickness: 0.188" nom.; counterbore depth: 0.125" nom.; counterbore dia.: 0.313" nom.

Material:

Copper alloy

Material Specification:

Mil-b-895, ships amend i, condition 1/2 hard military specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A521x0

Mil-std (military Standard):

Mil-b-895 spec.