NSN 3010-00-066-0555



| Gearcase-motor - Page 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/3010-00-066-0555 |
| Overall Height: |
| 1.062 inches |
| Overall Length: |
| 3.589 inches |
| Overall Width: |
| 1.062 inches |
| Spline Minor Diameter: |
| 0.108 inches single end |
| Spline Quantity: |
| 13 single end |
| Shaft Diameter: |
| 0.1247 inches single end |
| Current Type: |
| Ac input |
| Shaft Rotation Direction: |
| Counterclockwise single end |
| Duty Cycle: |
| Continuous |
| Inclosure Feature: |
| Totally enclosed |
| Winding Type: |
| Induction-single value capacitor split phase |
| Spline Length: |
| 0.3950 inches single end |
| Mounting Method: |
| Clamp ring |
| Mounting Facility Type And Quantity: |
| 1 clamp collar |
| Geared Head Output Shaft Alignment Position: |
| Inline w/armature single end |
| Cooling Method: |
| Nonventilated |
| Current Rating Method: |
| Load |
| |

Torque Rating And Type:

3.0 inch-ounces running

Speed Control Method And Device Type:

Automatic mechanical

Inclosure Specificationification:

Commercial

Features Provided:

Horizontal mounting position and vertical mounting position

NSN 3010-00-066-0555 Gearcase-motor - Page 2 of 2



| Power Rating: | |
|---|--|
| 3.5000 watts output | |
| Length Of Shaft From Housing: | |
| 0.395 inches single end | |
| Mounting Facility Circle Diameter: | |
| 0.812 inches | |
| Current Rating In Amps: | |
| 0.049 single output | |
| Connection Type And Voltage Rating In Volts: | |
| 115.0 line to neutral low input or 180.0 line to neutral high input | |
| Geared Head Output Shaft Speed Rating: | |
| 3.300 single revolutions per minute single end | |
| Shaft End Characteristic: | |
| A14 single style single end | |
| Phase: | |
| Two input | |
| Frequency In Hertz: | |
| 400.0 input | |
| Terminal Type And Quantity: | |
| 10 wire lead | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| . | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A271a0 | |
| | |