NSN 3010-00-116-1032

Gearcase-motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3010-00-116-1032

| Overall Height: |
|---|
| 3.500 inches |
| Overall Length: |
| 6.000 inches |
| Overall Width: |
| 3.500 inches |
| Shaft Diameter: |
| 0.1570 inches single end |
| Current Type: |
| Ac input |
| Shaft Rotation Direction: |
| Clockwise single end or counterclockwise single end |
| Duty Cycle: |
| Continuous |
| Inclosure Feature: |
| Dustproof |
| Winding Type: |
| Repulsion-induction |
| Mounting Method: |
| Flange |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Geared Head Output Shaft Alignment Position: |
| Offset below parallel to shaft axis single end |
| Cooling Method: |
| Nonventilated |
| Current Rating Method: |
| Load |
| Features Provided: |
| Vertical mounting position |
| Length Of Shaft From Housing: |
| 1.250 inches single end |
| Tempurature Rating: |
| -20.0 operating degrees celsius and 50.0 operating degrees celsius and 50.0 ambient degrees celsius |
| Mounting Facility Circle Diameter: |
| 2.437 inches |
| Current Rating In Amps: |
| 0.120 single output |
| Connection Type And Voltage Rating In Volts: |
| 115.0 line to neutral single input |
| Geared Head Output Shaft Speed Rating: |

875.000 single revolutions per minute single end

NSN 3010-00-116-1032

Gearcase-motor - Page 2 of 2



| Shaft End Characteristic: |
|-----------------------------|
| A1 single style single end |
| Phase: |
| Single input |
| Frequency In Hertz: |
| 60.0 input |
| Terminal Type And Quantity: |
| 4 solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: A271a0