

View Online at <https://aerobasegroup.com/nsn/3010-00-153-2454>

Body Style:

Flexible keyway insert type, through bore

Spline Major Diameter:

Between 0.874 inches and 0.875 inches

Overall Length:

Between 2.172 inches and 2.187 inches

Outside Diameter:

Between 3.240 inches and 3.260 inches

Spline Quantity:

6

Bore Shape:

Splined

Special Features:

W/external keyway 0.374" minus 0.000 plus 0.001 w; distance from bore centerline to body keying facility bottom/top: 1.125" nom.; body keying facility dep/ht: 0.687" nom.; body keying facility wd: 0.7495" min.0.7500" max.; bore counterbore feature: included; keying facility: not included; counterbore location: coupling end; spline lg.: 1.281" min., 1.311" max.; hub od: 1.5001" min., 1.5006" max.; thread provision: unthreaded; bore lg.: 1/2" nom.; flange thickness: 1.312" nom.; counterbore dep.: 0.125" nom., 0.079" nom.; counterbore dia.: 1.125"min., 1.400" max.; spline minor dia.: 0.743" min., 0.744" max.

Material:

Steel

Material Specification:

Mil-s-890, class alloy no. 3 military specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A521x0

Mil-std (military Standard):

Mil-s-890 spec.