

View Online at <https://aerobasegroup.com/nsn/3010-00-214-1839>

Body Style:

Flexible keyway insert type, through bore

Overall Length:

Between 0.870 inches and 0.878 inches

Outside Diameter:

Between 0.984 inches and 1.016 inches

Bore Diameter:

Between 0.2500 inches and 0.2502 inches

Bore Length:

Between 0.5210 inches and 0.5310 inches

Bore Shape:

Straight

Special Features:

Hub stepped down to 1/2" porm 1/64 dia. By 7/16" porm 1/64 lg, one 5/32" by 0.260" porm .005 slot between bore and bounterbore; distance from bore centerline to body keying facility bottom/top: 0.281" nom.; body keying facility wd: 0.3125" min., 0.3128" max.; body keying facility dep/ht: 0.060" min., 0.068" max.; bore counterbore feature: included; keying facility: not included; counterbore location: coupling end; hub od: 0.734" min., 0.766" max.; thread provision: unthreaded; flange thickness: 0.109" min., 0.141" max.; counterbore depth: 0.208" min., 0.218" max.; counterbore dia.: 0.546" min., 0.578" max.

Material:

Steel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A521x0