## NSN 3010-00-252-0029

Rigid Shaft Coupling - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3010-00-252-0029

Overall Length:
4.000 inches
Overall Diameter:
Between 3.936 inches and 3.940 inches
Bore Shape:
Tapered both ends
Features Provided:
Keyway and bore counterbore
Taper Largest Diameter:
0.8715 inches first end and 0.8720 inches first end
Body Material:
Steel
Special Features:
Between counterbore diameter: first end, 1.188 in.; second end, 2.438 in. And 2.439 in. and 1.188 in.; counterbore depth: first end,
0.562 in.; second end, 0.094 in. And 0.750 in.; taper length: first end, 2.062 in.; second end, 2.000 in.; distance from center of bore to
bottom of keyway: first end, 0.529 in., second end 0.52325 in.; flange width: 1.125 in.; taper per foot: both ends, 0.602 in. Nomial; hub
diameter: 2.125 in.; 1 keying facility provided at each end; keying facility width: both ends, 0.188 in.; keying facility length: first end,
1.500 in., second end, 1.250 in.; raised face one half 2-7/16 in. Dia, 1/16 in. Thk; furnished items: 4 finished bolts, 4 hex nuts
Style Designator:
Plain flange
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A522c0