## NSN 3010-00-252-7635

Flexible Shaft Coupling - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3010-00-252-7635

**Hole Diameter:** 0.082 inches both ends **Spline Minor Diameter:** 0.2320 inches second end **Spline Major Diameter:** 0.2610 inches second end **Counterbore Diameter:** 0.2700 inches both ends **Counterbore Depth:** 0.2475 inches both ends **Overall Length:** Between 1.437 inches and 1.452 inches **Outside Diameter:** 0.843 inches **Taper Minor Diameter:** 0.3750 inches both ends **Spline Quantity:** 19 both ends **Thread Size Designator:** No. 6/0.138 in./-32 thd size both ends **Bore Diameter:** 0.3750 inches both ends **Bore Length:** 0.3900 inches both ends **Bore Shape:** Tapered second end **Bellows Material:** Stainless steel **Design Type: Bellows** Spline Length: 0.250 inches both ends **Securing Method:** Threaded hole first end **Threaded Hole Quantity:** 1 both ends **Threaded Hole Location:** Both ends: one hole located 90 degrees from unthreaded hole **Unthreaded Hole Quantity:** 2 both ends **Features Provided:** 

Counterbore

## NSN 3010-00-252-7635

Flexible Shaft Coupling - Page 2 of 2



T	aper	Largest	Diameter:

0.3750 inches both ends

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A522b0