## NSN 3010-00-273-1766

Shaft Coupling Half - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3010-00-273-1766

| Body Style:  |  |
|--|--|
| 2 hole flange, through bore  |  |
| Spline Major Diameter:   |  |
| Between 0.624 inches and 0.625 inches  |  |
| Overall Length:  |  |
| Between 0.740 inches and 0.760 inches  |  |
| Spline Quantity:   |  |
| 3  |  |
| Bore Length:   |  |
| 0.6500 inches  |  |
| Bore Shape:  |  |
| Splined  |  |
| Special Features:  |  |
| Unthreaded bore dia.: 0.3750" min., 0.3754" max.; positioning facility bolt circle dia.:   | 2.098" min., 2.102" max.; positioning facility qty: 2; |
| positioning hole style: plain; bore counterbore feature: not included; keying facility: no | ot included; o/a outside dimension: 2.850" nom.;       |
| spline lg.: 0.650" nom.; hub od: 1.240" min., 1.260" max.; thread provision: unthread      | ded; flange thickness: 0.540" min., 0.560" max.; splin |
| minor dia.: 0.530" min., 0.531" max.   |  |
| Material:  |  |
| Steel  |  |
| Material Specification:  |  |
| Sae 1020 carbon assn standard single material response                                     |  |
| Shelf Life:  |  |
| N/a  |  |
| Unit Of Measure:   |  |
| -  |  |
| Demilitarization:  |  |
| No   |  |
| Fiig:  |  |
| A521x0   |  |