## NSN 3010-00-273-3855

Shaft Coupling Half - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3010-00-273-3855

Body Style:
Flexible keyway insert type, through bore
Overall Length:
Between 0.740 inches and 0.760 inches
Bore Diameter:
Between 0.6250 inches and 0.6255 inches
Bore Length:
0.5500 inches
Bore Shape:
Straight
Special Features:
Distance from bore centerline to body keying facility bottom/top: 0.625" nom.; body keying facility depth/ht: 0.198" min., 0.202" max.; body
keying facility wd: 0.250" nom.; bore counterbore feature: not included; keying facility type: integral key; keying facility qty: 1; keying
facility: included; o/a outside dimension: 1.937" nom.; hub od: 0.990" min., 1.010" max.; thread provision: unthreaded; distance form
center of bore to top of key: 0.2015" nom.; key wd: 0.187" min., 0.188" max.; flange thickness: 0.140" min., 0.160" max.; material: carbo
steel
Material Specification:
Mil-s-890, class b-s special military specification single material response
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A521x0
Mil-std (military Standard):
Mil-s-890 spec.