

View Online at <https://aerobasegroup.com/nsn/3010-00-273-4200>

**Body Style:**

Flexible keyway insert type, through bore

**Overall Length:**

Between 1.050 inches and 1.070 inches

**Bore Diameter:**

Between 0.5000 inches and 0.5005 inches

**Bore Length:**

0.8100 inches

**Bore Shape:**

Straight

**Special Features:**

Center lines of internal keys and external keys on same plane; distance from bore counterbore to body keying facility bottom/top; body keying facility depth/ht: 0.240" min., 0.250" max.; body keying facility wd: 0.4995" min., 0.4998" max.; bore counterbore feature: included; keying facility type: keyway; keying facility spacing in deg.: 180; keying facility qty: 2; keying facility: included; counterbore location: coupling end; o/a outside dimension: 2" porm .010"; hub od: 0.990" min., 1.010" max.; thread provision: unthreaded; distance from center of bore to bottom of keyway: 0.183" nom.; distance from center of bore to top of key: a/a; key wd: 0.125" nom.; flange thickness: 0.600" nom.; counterbore depth: 0.040" min., 0.060" max.; counterbore dia.: 1.240" min., 1.260" max.

**Material:**

Copper alloy

**Material Specification:**

Mil-b-994, comp a, half-hard military specification single material response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A521x0

**Mil-std (military Standard):**

Mil-b-994 spec.