

View Online at <https://aerobasegroup.com/nsn/3010-00-277-1103>

Body Style:

Multiple positioning holes, raised face

Overall Length:

2.281 inches

Bore Length:

2.2810 inches

Bore Shape:

Tapered

Taper Largest Diameter:

Between 0.8475 inches and 0.8750 inches

Special Features:

Unthreaded bore dia.: 0.484" nom.; raised face thickness: 0.063" nom.; positioning facility bolt circle dia.: 3.250" nom.; positioning facility qty: 3; positioning hole style: plain; bore counterbore feature: included; keying facility type: keyway; keying facility qty: 1; keying facility: included; counterbore location: coupling end; o/a outside dimension: 4.250" nom.; hub od: 1.750" nom.; raised face dia.: 2.2485" min., 2.2490" max.; thread provision: unthreaded; distance from center of bore to bottom of keyway: 0.53125" nom.; keyway wd: 0.188" nom.; taper minor dia.: 0.7118" min., 0.7123" max.; flange thickness: 1/2" nom.; counterbore depth: 0.656" nom.; counterbore dia.: 1.750" nom.

Material:

Steel

Material Specification:

Mil-s-15083, cl b military specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A521x0

Mil-std (military Standard):

Mil-s-15083 spec.