NSN 3010-00-289-7843

Shaft Coupling Half - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3010-00-289-7843

1.531 inches Bore Diameter: Between 0.9905 inches and 0.9915 inches Bore Length: 1.0940 inches Bore Shape: Straight Features Provided: Keyway Special Features: Body keying facility depth/height: 0.125" nom.; body keying facility width: 0.438" nom.; hole thread size designator: 1/4 - 20; threaded hole location: located 90 deg. From keyway; threaded hole qty: 1; securing method: threaded hole; bore counterbore feature: not included; keying facility qty: 1; o/a outside dimension: 3.125" nom.; hub od: 1.500" nom.; groove od: 1.625" nom.; thread provision: unthreaded; distance from center of bore to bottom of keyway: 0.594" nom.; keyway width: 0.1875" nom.; flange thickness: 0.656" nom.; groove depth: 0.469" nom. Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Bore Diameter: Between 0.9905 inches and 0.9915 inches Bore Length: 1.0940 inches Bore Shape: Straight Features Provided: Keyway Special Features: Body keying facility depth/height: 0.125* nom.; body keying facility width: 0.438* nom.; hole thread size designator: 1/4 - 20; threaded hole location: located 90 deg. From keyway; threaded hole qty: 1; securing method: threaded hole; bore counterbore feature: not included; keying facility up: 1; o/a outside dimension: 3.125* nom.; hub od: 1.500* nom.; groove od: 1.625* nom.; thread provision: unthreaded; distance from center of bore to bottom of keyway: 0.594* nom.; keyway width: 0.1875* nom.; flange thickness: 0.656* nom.; groove depth: 0.469* nom. Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Overall Length:
Between 0.9905 inches and 0.9915 inches Bore Length: 1.0940 inches Bore Shape: Straight Features Provided: Keyway Special Features: Body keying facility depth/height: 0.125" nom.; body keying facility width: 0.438" nom.; hole thread size designator: 1/4 - 20; threaded hole location: located 90 deg. From keyway; threaded hole qty: 1; securing method: threaded hole; bore counterbore feature: not included; keying facility qty: 1; o/a outside dimension: 3.125" nom.; hub od: 1.500" nom.; groove od: 1.625" nom.; thread provision: unthreaded; distance from center of bore to bottom of keyway: 0.594" nom.; keyway width: 0.1875" nom.; flange thickness: 0.656" nom.; groove depth: 0.469" nom. Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1.531 inches
Bore Length: 1.0940 inches Bore Shape: Straight Features Provided: Keyway Special Features: Body keying facility depth/height: 0.125" nom.; body keying facility width: 0.438" nom.; hole thread size designator: 1/4 - 20; threaded hole location: located 90 deg. From keyway; threaded hole qty: 1; securing method: threaded hole; bore counterbore feature: not included; keying facility qty: 1; o/a outside dimension: 3.125" nom.; hub od: 1.500" nom.; groove od: 1.625" nom.; thread provision: unthreaded; distance from center of bore to bottom of keyway: 0.594" nom.; keyway width: 0.1875" nom.; flange thickness: 0.656" nom.; groove depth: 0.469" nom. Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Bore Diameter:
1.0940 inches Bore Shape: Straight Features Provided: Keyway Special Features: Body keying facility depth/height: 0.125" nom.; body keying facility width: 0.438" nom.; hole thread size designator: 1/4 - 20; threaded hole location: located 90 deg. From keyway; threaded hole qty: 1; securing method: threaded hole; bore counterbore feature: not included; keying facility qty: 1; o/a outside dimension: 3.125" nom.; hub od: 1.500" nom.; groove od: 1.625" nom.; thread provision: unthreaded; distance from center of bore to bottom of keyway: 0.594" nom.; keyway width: 0.1875" nom.; flange thickness: 0.656" nom.; groove depth: 0.469" nom. Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.9905 inches and 0.9915 inches
Bore Shape: Straight Features Provided: Keyway Special Features: Body keying facility depth/height: 0.125" nom.; body keying facility width: 0.438" nom.; hole thread size designator: 1/4 - 20; threaded hole location: located 90 deg. From keyway; threaded hole qty: 1; securing method: threaded hole; bore counterbore feature: not included; keying facility qty: 1; o/a outside dimension: 3.125" nom.; hub od: 1.500" nom.; groove od: 1.625" nom.; thread provision: unthreaded; distance from center of bore to bottom of keyway: 0.594" nom.; keyway width: 0.1875" nom.; flange thickness: 0.656" nom.; groove depth: 0.469" nom. Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Bore Length:
Straight Features Provided: Keyway Special Features: Body keying facility depth/height: 0.125" nom.; body keying facility width: 0.438" nom.; hole thread size designator: 1/4 - 20; threaded hole location: located 90 deg. From keyway; threaded hole qty: 1; securing method: threaded hole; bore counterbore feature: not included; keying facility qty: 1; o/a outside dimension: 3.125" nom.; hub od: 1.500" nom.; groove od: 1.625" nom.; thread provision: unthreaded; distance from center of bore to bottom of keyway: 0.594" nom.; keyway width: 0.1875" nom.; flange thickness: 0.656" nom.; groove depth: 0.469" nom. Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1.0940 inches
Features Provided: Keyway Special Features: Body keying facility depth/height: 0.125" nom.; body keying facility width: 0.438" nom.; hole thread size designator: 1/4 - 20; threaded hole location: located 90 deg. From keyway; threaded hole qty: 1; securing method: threaded hole; bore counterbore feature: not included; keying facility qty: 1; o/a outside dimension: 3.125" nom.; hub od: 1.500" nom.; groove od: 1.625" nom.; thread provision: unthreaded; distance from center of bore to bottom of keyway: 0.594" nom.; keyway width: 0.1875" nom.; flange thickness: 0.656" nom.; groove depth: 0.469" nom. Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No	Bore Shape:
Special Features: Body keying facility depth/height: 0.125" nom.; body keying facility width: 0.438" nom.; hole thread size designator: 1/4 - 20; threaded hole location: located 90 deg. From keyway; threaded hole qty: 1; securing method: threaded hole; bore counterbore feature: not included; keying facility qty: 1; o/a outside dimension: 3.125" nom.; hub od: 1.500" nom.; groove od: 1.625" nom.; thread provision: unthreaded; distance from center of bore to bottom of keyway: 0.594" nom.; keyway width: 0.1875" nom.; flange thickness: 0.656" nom.; groove depth: 0.469" nom. Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Straight
Special Features: Body keying facility depth/height: 0.125" nom.; body keying facility width: 0.438" nom.; hole thread size designator: 1/4 - 20; threaded hole location: located 90 deg. From keyway; threaded hole qty: 1; securing method: threaded hole; bore counterbore feature: not included; keying facility qty: 1; o/a outside dimension: 3.125" nom.; hub od: 1.500" nom.; groove od: 1.625" nom.; thread provision: unthreaded; distance from center of bore to bottom of keyway: 0.594" nom.; keyway width: 0.1875" nom.; flange thickness: 0.656" nom.; groove depth: 0.469" nom. Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Features Provided:
Body keying facility depth/height: 0.125" nom.; body keying facility width: 0.438" nom.; hole thread size designator: 1/4 - 20; threaded hole location: located 90 deg. From keyway; threaded hole qty: 1; securing method: threaded hole; bore counterbore feature: not included; keying facility qty: 1; o/a outside dimension: 3.125" nom.; hub od: 1.500" nom.; groove od: 1.625" nom.; thread provision: unthreaded; distance from center of bore to bottom of keyway: 0.594" nom.; keyway width: 0.1875" nom.; flange thickness: 0.656" nom.; groove depth: 0.469" nom. Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Keyway
location: located 90 deg. From keyway; threaded hole qty: 1; securing method: threaded hole; bore counterbore feature: not included; keying facility qty: 1; o/a outside dimension: 3.125" nom.; hub od: 1.500" nom.; groove od: 1.625" nom.; thread provision: unthreaded; distance from center of bore to bottom of keyway: 0.594" nom.; keyway width: 0.1875" nom.; flange thickness: 0.656" nom.; groove depth: 0.469" nom. Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Special Features:
keying facility qty: 1; o/a outside dimension: 3.125" nom.; hub od: 1.500" nom.; groove od: 1.625" nom.; thread provision: unthreaded; distance from center of bore to bottom of keyway: 0.594" nom.; keyway width: 0.1875" nom.; flange thickness: 0.656" nom.; groove depth: 0.469" nom. Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body keying facility depth/height: 0.125" nom.; body keying facility width: 0.438" nom.; hole thread size designator: 1/4 - 20; threaded hole
distance from center of bore to bottom of keyway: 0.594" nom.; keyway width: 0.1875" nom.; flange thickness: 0.656" nom.; groove depth: 0.469" nom. Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	location: located 90 deg. From keyway; threaded hole qty: 1; securing method: threaded hole; bore counterbore feature: not included;
0.469" nom. Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	keying facility qty: 1; o/a outside dimension: 3.125" nom.; hub od: 1.500" nom.; groove od: 1.625" nom.; thread provision: unthreaded;
Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	distance from center of bore to bottom of keyway: 0.594" nom.; keyway width: 0.1875" nom.; flange thickness: 0.656" nom.; groove depth
Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.469" nom.
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
N/a Unit Of Measure: Demilitarization: No Filig:	Copper alloy
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A521x0	Fiig:
	A521x0