

View Online at <https://aerobasegroup.com/nsn/3010-00-294-5554>

Overall Length:

Between 0.451 inches and 0.455 inches

Outside Diameter:

Between 1.560 inches and 1.561 inches

Bore Diameter:

Between 0.4375 inches and 0.4385 inches

Bore Length:

Between 0.1700 inches and 0.1740 inches

Bore Shape:

Straight

Special Features:

Surface treatment: passivated; unthreaded bore depth: 0.920" min., 0.960" max.; unthreaded bore dia.: 0.203" nom.; bore thread size designator: 6-32 nc; positioning facility bolt circle dia.: 1.281" nom.; positioning facility qty: 2; body keying facility dep/ht: 0.281" nom.; body keying facility wd: 0.2500" min., 0.2505" max.; positioning hole style: tapped; securing method: key; keying facility and bore counterbore feature: not included; hub od: 0.623" min., 0.624" max.; thread provision: unthreaded; flange thickness: 0.920" min., 0.960" max.

Material:

Stainless steel

Material Specification:

Mil-s-853a, cl 7, ty a military specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A521x0

Mil-std (military Standard):

Mil-s-853a spec.