

View Online at <https://aerobasegroup.com/nsn/3010-00-294-5554>

**Overall Length:**

Between 0.451 inches and 0.455 inches

**Outside Diameter:**

Between 1.560 inches and 1.561 inches

**Bore Diameter:**

Between 0.4375 inches and 0.4385 inches

**Bore Length:**

Between 0.1700 inches and 0.1740 inches

**Bore Shape:**

Straight

**Special Features:**

Surface treatment: passivated; unthreaded bore depth: 0.920" min., 0.960" max.; unthreaded bore dia.: 0.203" nom.; bore thread size designator: 6-32 nc; positioning facility bolt circle dia.: 1.281" nom.; positioning facility qty: 2; body keying facility dep/ht: 0.281" nom.; body keying facility wd: 0.2500" min., 0.2505" max.; positioning hole style: tapped; securing method: key; keying facility and bore counterbore feature: not included; hub od: 0.623" min., 0.624" max.; thread provision: unthreaded; flange thickness: 0.920" min., 0.960" max.

**Material:**

Stainless steel

**Material Specification:**

Mil-s-853a, cl 7, ty a military specification single material response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A521x0

**Mil-std (military Standard):**

Mil-s-853a spec.