NSN 3010-00-294-8858

Rigid Shaft Coupling - Page 1 of 1

A522c0



View Online at https://aerobasegroup.com/nsn/3010-00-294-8858
Overall Length:
Between 3.120 inches and 3.126 inches
Overall Diameter:
Between 4.495 inches and 4.500 inches
Bore Shape:
Tapered both ends
Features Provided:
Keyway and bore counterbore
Taper Largest Diameter:
0.7495 inches first end and 0.7500 inches first end
Body Material:
Steel
Special Features:
Between 8large end of coupling has raised face, 2.249 in. Plus 0.000 minus 0.001 diameter and 1/16 in. H which fits into second step of
counterbore on small end of coupling; counterbore dia: first end, 1.625 in.; second end, 2.250 in. And 2.251 in.; counterbore depth: first
end, 0.438 in.; second end, 0.375 and 0.125 in.; taper length: first end, 1.625 in.; second end, 1.560 in. And 1.563 in.; distance from
center of bore to bottom of keyway: 0.484 in.; flange width: 1.125 in.; furnished items: 4 bolts, 4 nuts, 4 jam nuts; taper per foot, both
ends, 0.500 in.; hub diameter: 2.000 in.; 1 keying facility provided; keying facility width: 0.188 in.; keying facility length: 1.188 in.
Style Designator:
Plain flange
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: