## NSN 3010-00-294-8860

Rigid Shaft Coupling - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3010-00-294-8860

Overall Diameter:  12.000 inches  Bore Shape:  Tapered both ends  Features Provided:  Keyway and bore counterbore  Taper Largest Diameter:  3.4995 inches first end and 3.5000 inches first end  Body Material:  Steel  Special Features:  Largest bore half of coupling has a raised face 1/8 in. Thk, 5.499in. Dim., designed to fit into counterbore of other half, hub tapered to 6 in.C both ends; counterbore diameter: first end, 4.500 and 4.750 in.; second end, 5.500 and 4.500 in.; counterbore depth: first end, 0.750 and 0.250 in.; second end, 0.781 and 0.156 in.; taper length: first end. 5.625 in. And second end, 4.938 in.; distance from center of bore to bottom of keyway: first end, 2.0625 in.; second end, 1.7495-1.7500 in.; flange width: 3.875 in.; taper per foot: both ends, 0.62 in.; shub diameter: 5.750 in.; 1 keying facility at each end; keying facility width: both ends, 0.750; keying facility length: first end, 4.625 in., second end, 4.000 in.  Style Designator:  Plain flange  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Flig:	Overall Length:
12.000 inches  Bore Shape: Tapered both ends  Features Provided: Keyway and bore counterbore  Taper Largest Diameter: 3.4995 inches first end and 3.5000 inches first end  Body Material: Steel  Special Features: Largest bore half of coupling has a raised face 1/8 in. Thk, 5.499in. Dim., designed to fit into counterbore of other half, hub tapered to 6 in.C both ends; counterbore diameter: first end, 4.500 and 4.750 in.; second end, 5.500 and 4.500 in.; counterbore depth: first end, 0.750 and 0.250 in.; second end, 0.781 and 0.156 in.; taper length: first end. 5.625 in. And second end, 4.938 in.; distance from center of bore to bottom of keyway: first end, 2.0625 in.; second end, 1.7495-1.7500 in.; flange width: 3.875 in.; taper per foot: both ends, 0.62 in.; hub diameter: 5.750 in.; 1 keying facility at each end; keying facility width: both ends, 0.750; keying facility length: first end, 4.625 in., second end, 4.000 in.  Style Designator: Plain flange  Shelf Life: N/a  Unit Of Measure:   Demilitarization: No  Fig:	10.438 inches
Bore Shape: Tapered both ends Features Provided: Keyway and bore counterbore Taper Largest Diameter: 3.4995 inches first end and 3.5000 inches first end Body Material: Steel Special Features: Largest bore half of coupling has a raised face 1/8 in. Thk, 5.499in. Dim., designed to fit into counterbore of other half, hub tapered to 6 in.C both ends; counterbore diameter: first end, 4.500 and 4.750 in.; second end, 5.500 and 4.500 in.; counterbore depth: first end, 0.750 and 0.250 in.; second end, 0.781 and 0.156 in.; taper length: first end, 5.625 in. And second end, 4.938 in.; distance from center of bore to bottom of keyway: first end, 2.0625 in.; second end, 1.7495-1.7500 in.; flange width: 3.875 in.; taper per foot: both ends, 0.62 in., second end, 4.000 in. Style Designator: Plain flange Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Overall Diameter:
Tapered both ends  Features Provided:  Keyway and bore counterbore  Taper Largest Diameter:  3.4995 inches first end and 3.5000 inches first end  Body Material:  Steel  Special Features:  Largest bore half of coupling has a raised face 1/8 in. Thk, 5.499in. Dim., designed to fit into counterbore of other half, hub tapered to 6 in.C both ends; counterbore diameter: first end, 4.500 and 4.750 in.; second end, 5.500 and 4.500 in.; counterbore depth: first end, 0.750 and 0.250 in.; second end, 0.781 and 0.156 in.; taper length: first end. 5.625 in. And second end, 4.938 in.; distance from center of bore to bottom of keyway: first end, 2.0625 in.; second end, 1.7495-1.7500 in.; flange width: 3.875 in.; taper per foot: both ends, 0.62 in.; second end, 4.000 in.  Style Designator:  Plain flange  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	12.000 inches
Features Provided: Keyway and bore counterbore Taper Largest Diameter: 3.4995 inches first end and 3.5000 inches first end Body Material: Steel Special Features: Largest bore half of coupling has a raised face 1/8 in. Thk, 5.499in. Dim., designed to fit into counterbore of other half, hub tapered to 6 in.C both ends; counterbore diameter: first end, 4.500 and 4.750 in.; second end, 5.500 and 4.500 in.; counterbore depth: first end, 0.750 and 0.250 in.; second end, 0.781 and 0.156 in.; taper length: first end. 5.625 in. And second end, 4.938 in.; distance from center of bore to bottom of keyway: first end, 2.0625 in.; second end, 1.7495-1.7500 in.; flange width: 3.875 in.; taper per foot: both ends, 0.62 in.; hub diameter: 5.750 in.; 1 keying facility at each end; keying facility width: both ends, 0.750; keying facility length: first end, 4.625 in., second end, 4.000 in.  Style Designator: Plain flange Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Bore Shape:
Keyway and bore counterbore  Taper Largest Diameter: 3.4995 inches first end and 3.5000 inches first end  Body Material:  Steel  Special Features:  Largest bore half of coupling has a raised face 1/8 in. Thk, 5.499in. Dim., designed to fit into counterbore of other half, hub tapered to 6 in.C both ends; counterbore diameter: first end, 4.500 and 4.750 in.; second end, 5.500 and 4.500 in.; counterbore depth: first end, 0.750 and 0.250 in.; second end, 0.781 and 0.156 in.; taper length: first end. 5.625 in. And second end, 4.938 in.; distance from center of bore to bottom of keyway: first end, 2.0625 in.; second end, 1.7495-1.7500 in.; flange width: 3.875 in.; taper per foot: both ends, 0.62 in.; hub diameter: 5.750 in.; 1 keying facility at each end; keying facility width: both ends, 0.750; keying facility length: first end, 4.625 in., second end, 4.000 in.  Style Designator:  Plain flange  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Tapered both ends
Taper Largest Diameter: 3.4995 inches first end and 3.5000 inches first end  Body Material: Steel  Special Features:  Largest bore half of coupling has a raised face 1/8 in. Thk, 5.499in. Dim., designed to fit into counterbore of other half, hub tapered to 6 in.C both ends; counterbore diameter: first end, 4.500 and 4.750 in.; second end, 5.500 and 4.500 in.; counterbore depth: first end, 0.750 and 0.250 in.; second end, 0.781 and 0.156 in.; taper length: first end. 5.625 in. And second end, 4.938 in.; distance from center of bore to bottom of keyway: first end, 2.0625 in.; second end, 1.7495-1.7500 in.; flange width: 3.875 in.; taper per foot: both ends, 0.62 in.; hub diameter: 5.750 in.; 1 keying facility at each end; keying facility width: both ends, 0.750; keying facility length: first end, 4.625 in., second end, 4.000 in.  Style Designator:  Plain flange  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Features Provided:
3.4995 inches first end and 3.5000 inches first end  Body Material:  Steel  Special Features:  Largest bore half of coupling has a raised face 1/8 in. Thk, 5.499in. Dim., designed to fit into counterbore of other half, hub tapered to 6 in.C both ends; counterbore diameter: first end, 4.500 and 4.750 in.; second end, 5.500 and 4.500 in.; counterbore depth: first end, 0.750 and 0.250 in.; second end, 0.781 and 0.156 in.; taper length: first end. 5.625 in. And second end, 4.938 in.; distance from center of bore to bottom of keyway: first end, 2.0625 in.; second end, 1.7495-1.7500 in.; flange width: 3.875 in.; taper per foot: both ends, 0.62 in.; hub diameter: 5.750 in.; 1 keying facility at each end; keying facility width: both ends, 0.750; keying facility length: first end, 4.625 in., second end, 4.000 in.  Style Designator:  Plain flange  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Keyway and bore counterbore
Body Material:  Steel  Special Features:  Largest bore half of coupling has a raised face 1/8 in. Thk, 5.499in. Dim., designed to fit into counterbore of other half, hub tapered to 6 in.C both ends; counterbore diameter: first end, 4.500 and 4.750 in.; second end, 5.500 and 4.500 in.; counterbore depth: first end, 0.750 and 0.250 in.; second end, 0.781 and 0.156 in.; taper length: first end. 5.625 in. And second end, 4.938 in.; distance from center of bore to bottom of keyway: first end, 2.0625 in.; second end, 1.7495-1.7500 in.; flange width: 3.875 in.; taper per foot: both ends, 0.62 in.; hub diameter: 5.750 in.; 1 keying facility at each end; keying facility width: both ends, 0.750; keying facility length: first end, 4.625 in., second end, 4.000 in.  Style Designator:  Plain flange  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Taper Largest Diameter:
Steel  Special Features:  Largest bore half of coupling has a raised face 1/8 in. Thk, 5.499in. Dim., designed to fit into counterbore of other half, hub tapered to 6 in. Coboth ends; counterbore diameter: first end, 4.500 and 4.750 in.; second end, 5.500 and 4.500 in.; counterbore depth: first end, 0.750 and 0.250 in.; second end, 0.781 and 0.156 in.; taper length: first end. 5.625 in. And second end, 4.938 in.; distance from center of bore to bottom of keyway: first end, 2.0625 in.; second end, 1.7495-1.7500 in.; flange width: 3.875 in.; taper per foot: both ends, 0.62 in.; hub diameter: 5.750 in.; 1 keying facility at each end; keying facility width: both ends, 0.750; keying facility length: first end, 4.625 in., second end, 4.000 in.  Style Designator:  Plain flange  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	3.4995 inches first end and 3.5000 inches first end
Special Features:  Largest bore half of coupling has a raised face 1/8 in. Thk, 5.499in. Dim., designed to fit into counterbore of other half, hub tapered to 6 in. C both ends; counterbore diameter: first end, 4.500 and 4.750 in.; second end, 5.500 and 4.500 in.; counterbore depth: first end, 0.750 and 0.250 in.; second end, 0.781 and 0.156 in.; taper length: first end. 5.625 in. And second end, 4.938 in.; distance from center of bore to bottom of keyway: first end, 2.0625 in.; second end, 1.7495-1.7500 in.; flange width: 3.875 in.; taper per foot: both ends, 0.62 in.; hub diameter: 5.750 in.; 1 keying facility at each end; keying facility width: both ends, 0.750; keying facility length: first end, 4.625 in., second end, 4.000 in.  Style Designator:  Plain flange  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Body Material:
Largest bore half of coupling has a raised face 1/8 in. Thk, 5.499in. Dim., designed to fit into counterbore of other half, hub tapered to 6 in. C both ends; counterbore diameter: first end, 4.500 and 4.750 in.; second end, 5.500 and 4.500 in.; counterbore depth: first end, 0.750 and 0.250 in.; second end, 0.781 and 0.156 in.; taper length: first end. 5.625 in. And second end, 4.938 in.; distance from center of bore to bottom of keyway: first end, 2.0625 in.; second end, 1.7495-1.7500 in.; flange width: 3.875 in.; taper per foot: both ends, 0.62 in.; hub diameter: 5.750 in.; 1 keying facility at each end; keying facility width: both ends, 0.750; keying facility length: first end, 4.625 in., second end, 4.000 in.  Style Designator:  Plain flange  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Steel
both ends; counterbore diameter: first end, 4.500 and 4.750 in.; second end, 5.500 and 4.500 in.; counterbore depth: first end, 0.750 and 0.250 in.; second end, 0.781 and 0.156 in.; taper length: first end. 5.625 in. And second end, 4.938 in.; distance from center of bore to bottom of keyway: first end, 2.0625 in.; second end, 1.7495-1.7500 in.; flange width: 3.875 in.; taper per foot: both ends, 0.62 in.; hub diameter: 5.750 in.; 1 keying facility at each end; keying facility width: both ends, 0.750; keying facility length: first end, 4.625 in., second end, 4.000 in.  Style Designator:  Plain flange  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Special Features:
N/a Unit Of Measure: Demilitarization: No Fiig:	both ends; counterbore diameter: first end, 4.500 and 4.750 in.; second end, 5.500 and 4.500 in.; counterbore depth: first end, 0.750 and 0.250 in.; second end, 0.781 and 0.156 in.; taper length: first end. 5.625 in. And second end, 4.938 in.; distance from center of bore to bottom of keyway: first end, 2.0625 in.; second end, 1.7495-1.7500 in.; flange width: 3.875 in.; taper per foot: both ends, 0.625 in.; hub diameter: 5.750 in.; 1 keying facility at each end; keying facility width: both ends, 0.750; keying facility length: first end, 4.625 in., second end, 4.000 in.  Style Designator:  Plain flange
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No  Fiig:	
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A522c0	Fiig:
	A522c0