

View Online at <https://aerobasegroup.com/nsn/3010-00-294-8869>

Body Style:

Multiple positioning holes, recessed face

Overall Length:

2.500 inches

Outside Diameter:

Between 7.620 inches and 7.630 inches

Bore Shape:

Tapered

Features Provided:

Keyway and counterbore

Taper Largest Diameter:

1.9960 inches

Special Features:

Cdistance from center of bore to bottom of keyway: 1.253" nom.; positioning hole counterbore dep.: 0.202" min., 0.218" max.; positioning hole counterbore dia.: 1.359" min., 1.391" max.; unthreaded bore dep.: 1.218" nom.; unthreaded bore dia.: 1.870" min., 1.875" max.; positioning facility bolt circle dia.: 6" nom.; positioning facility qty: 8; positioning hole style: counterbored; keying facility qty: 1; counterbore location: coupling end; hub od: 3.375" nom.; thread provision: unthreaded; bore lg.: 2.062" nom.; keyway wd.: 0.500" min., 0.501" max.; taper minor dia.: 1.924" nom.; recess dep: 0.4375" nom.; recess dia.: 3.125" nom.; flange thickness: 1.4375" nom.; counterbore dep: 0.03125" nom.; counterbore dia.: 7.375" nom.

Material:

Steel

Material Specification:

Mil-s-890, ships, class b military specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A521x0

Mil-std (military Standard):

Mil-s-890 spec.