

View Online at <https://aerobasegroup.com/nsn/3010-00-300-7995>

**Body Style:**

Flexible keyway insert type, through bore

**Overall Length:**

0.328 inches

**Bore Diameter:**

0.1560 inches

**Bore Length:**

0.2660 inches

**Bore Shape:**

Straight

**Special Features:**

Fsc application data (1) telescope, integrated with fire control equipment; surface treatment: passivated; offset distance between centerlines of bore and body keying facility: a/a; distance from bore centerline to body keying facility bottom/top: 0.1094" nom.; body keying facility depth/ht: 0.063" nom.; body keying facility wd: 0.125" nom.; hole thread size designator: 0.086" -64; unthreaded hole location: 90 deg. From thd hole; hole taper number: 6; unthreaded hole qty: 1; threaded hole location: on hub portion of coupling; threaded hole qty: 1; securing method: threaded hole and unthreaded hole; bore counterbore feature: not included; keying facility: not included; o/a outside dimension: 0.480" nom.; hub od: 0.375" nom.; thread provision: not included; flange thickness: 0.140" nom.

**Material:**

Steel

**Material Specification:**

Qq-s-763, cl 7, ty a federal specification single material response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A521x0