

View Online at <https://aerobasegroup.com/nsn/3010-00-350-4584>

Body Style:

Flexible key insert type, counterbored bore

Overall Length:

Between 0.947 inches and 0.957 inches

Bore Shape:

Tapered

Features Provided:

Keyway

Special Features:

Offset distance between bore centerline and body keying facility centerline 90 deg., porm 30 min.; fsc application data: magneto drive, gasoline engine, non-aircraft; body keying facility depth/height: 0.280" min. 0.290" max.; body keying facility width: 0.311" min., 0.312" max.; position hole style: tapered; bore counterbore feature: included; keying facility qty: 1; counterbore location: coupling end; o/a outside dimension: 1.640" nom.; taper hole major dia.: 0.587" min., 0.589" max.; keyway width: 0.126" min., 0.128" max.; taper major dia.: 0.587" min., 0.589" max.; taper minor dia.: 0.4628" min., 0.4661" max.; flange thickness: 0.417" min., 0.427" max.; taper hole minor dia.: 0.4628" min., 0.4661" max.; counterbore depth: 0.307" min., 0.327" max.; counterbore dia.: 1.080" nom.

Material:

Steel

Material Specification:

Qq-s-624a, fs 4340 federal specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A521x0