

View Online at <https://aerobasegroup.com/nsn/3010-00-350-4584>

**Body Style:**

Flexible key insert type, counterbored bore

**Overall Length:**

Between 0.947 inches and 0.957 inches

**Bore Shape:**

Tapered

**Features Provided:**

Keyway

**Special Features:**

Offset distance between bore centerline and body keying facility centerline 90 deg., porm 30 min.; fsc application data: magneto drive, gasoline engine, non-aircraft; body keying facility depth/height: 0.280" min. 0.290" max.; body keying facility width: 0.311" min., 0.312" max.; position hole style: tapered; bore counterbore feature: included; keying facility qty: 1; counterbore location: coupling end; o/a outside dimension: 1.640" nom.; taper hole major dia.: 0.587" min., 0.589" max.; keyway width: 0.126" min., 0.128" max.; taper major dia.: 0.587" min., 0.589" max.; taper minor dia.: 0.4628" min., 0.4661" max.; flange thickness: 0.417" min., 0.427" max.; taper hole minor dia.: 0.4628" min., 0.4661" max.; counterbore depth: 0.307" min., 0.327" max.; counterbore dia.: 1.080" nom.

**Material:**

Steel

**Material Specification:**

Qq-s-624a, fs 4340 federal specification single material response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A521x0