

View Online at <https://aerobasegroup.com/nsn/3010-00-391-9380>

Body Style:

Multiple positioning holes, recessed face

Overall Length:

14.563 inches

Bore Length:

10.8750 inches

Bore Shape:

Tapered

Features Provided:

Keyway

Taper Largest Diameter:

3.9260 inches

Special Features:

Unthreaded bore dia.: 0.938" nom.; positioning facility bolt circle dia.: 8.250" nom.; positioning facility qty: 6; positioning hole style: plain; securing method: unthreaded hole; bore counterbore feature: included; keying facility qty: 1; keying facility: included; counterbore location: coupling end; o/a outside dimension: 10.750" nom.; hub od: 5.250" nom.; furnished item and qty (6) engine coupling bolts, (6) hex nuts; thread provision: unthreaded; distance from center of bor to bottom of keyway: 2.306" nom.; key wd: 1" nom.; taper minor dia.: 3.246" nom.; recess depth: 0.438" nom.; recess dia.: 6" nom.; flange thickness: 1.313" nom.; counterbore depth: 3.688" nom.; couterbore dia.: 4.188" min., 5.125" max.

Material:

Copper alloy

Material Specification:

Mil-b-15939, composition 2 military specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A521x0

Mil-std (military Standard):

Mil-b-15939 spec.