Flexible Shaft Coupling - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3010-00-405-9705

Overall Length:	
6.938 inches	
Outside Diameter:	
5.438 inches	
Taper Minor Diameter:	
1.4840 inches second end	
Keyway Width:	
0.250 inches both ends	
Keyway Depth:	
0.1250 inches both ends	
Thread Size Designator:	
3/8 in24 both ends	
Bore Diameter:	
1.6250 inches first end and 1.6255 inches	s first end
Bore Length:	
2.0000 inches first end	
Bore Shape:	
Tapered second end	
Furnished Items And Quantity:	
Setscrews 2	
Design Type:	
Grid spring	
Keying Facility Quantity:	
1 both ends	
Keying Facility Type:	
Keyway both ends	
Securing Method:	
Threaded hole both ends	
Threaded Hole Quantity:	
2 both ends	
Threaded Hole Location:	
First end: one hole located on top of key;	second end: one hole located 90 degrees from keyway
Features Provided:	
Keyway and floating shaft	
Taper Largest Diameter:	
1.4850 inches second end	
Shelf Life:	
N/a	
Unit Of Measure:	
Demiliterization	
Demilitarization:	

NSN 3010-00-405-9705

Flexible Shaft Coupling - Page 2 of 2

Fiig: A522b0

