## NSN 3010-00-517-4618

Shaft Coupling Half - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3010-00-517-4618

| Body Style:   |
|---|
| Flexible keyway insert type, through bore   |
| Overall Length:   |
| 1.000 inches  |
| Outside Diameter:   |
| 2.000 inches  |
| Bore Diameter:  |
| 0.6260 inches   |
| Bore Shape:   |
| Straight  |
| Features Provided:  |
| Keyway and counterbore  |
| Special Features:   |
| Counterbore in securing hole at 0.375" dia. By 0.250" deep; distance from center of bore to bottom of keyway: 0.422" nom.; thread           |
| provision: unthreaded; body keying facility dep/ht: 0.375" nom.; body keying facility wd: 0.499" min., 0.500" max.; hole thread size        |
| designator: 1/4-20 nc-2; threaded hole location: 90 deg. Clockwise from keyway at 0.312" at center of bolt hole from hub end; threaded hole |
| qty: 1; securing method: threaded hole; keying facility qty: 1; counterbore location: coupling end; keyway wd: 0.1875" min., 0.1880" max.;  |
| counterbore dep.: 0.406" nom.; counterbore dia.: 1.312" nom.  |
| Material:   |
| Steel   |
| Material Specification:   |
| Qq-s-624 fs 4042 federal specification single material response   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A521x0  |
|   |