NSN 3010-00-528-0392



Nonvehicular Clutch Disk - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3010-00-528-0392 **Outside Diameter:** Between 16.719 inches and 16.750 inches Thickness: 0.120 inches **Material Thickness:** 0.094 inches **Bolt Hole Quantity: Bolt Hole Diameter:** 0.203 inches **Design Type:** Dry **Material Location:** Both sides **Design Form:** Solid **Bolt Hole Spacing:** 8 in.Bolt circle dia; 6-1/2 in.Bolt circle dia; 5-1/2 in.Bolt circle dia Disk Type: Plain **Asbestos Composition Type:** Woven **Material Outside Diameter:** Between 16.719 inches and 16.750 inches **Material Inside Diameter:** Between 11.250 inches and 11.281 inches **Facing Attachment Method:** Bonded **Features Provided:** Friction material facing Construction: Solid **Disk Material:** Steel **Special Features:** 4 holes on 8 in.Bolt circle located on verticalcenter line 90 degrees apart; 12 holes on 6-1/2 in. Bolt circle 0.314 in.Min.0.320 in.Max.Located 15 deg.From vertical center line 30 deg.Apart; 12 holes on 5-1/2 in.Bolt circle 0.314 in.Min. 0.320 max.Located on vertical center line 30 deg.Apart; flexdb; matldas0000; bolt hole included; asbestos composition: woven Flexibility: Rigid

N/a

Material: Asbestos Shelf Life:

NSN 3010-00-528-0392

Nonvehicular Clutch Disk - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A521p0