NSN 3010-00-528-4949

Shaft Coupling Half - Page 1 of 1



view Online at https://aerobasegroup.com/nsn/3010-00-528-4949
Body Style:
Flexible keyway insert type, through bore
Overall Length:
Between 0.990 inches and 1.010 inches
Outside Diameter:
Between 1.990 inches and 2.010 inches
Bore Diameter:
Between 0.7500 inches and 0.7510 inches
Bore Shape:
Straight
Features Provided:
Keyway and counterbore
Special Features:
Counterbore in securing hole at 0.375" dia. By 0.250" deep; body keying facility dep/ht: 0.365" min., 0.385" max.; body keying facility wd:
0.499" min., 0.500 " max.; hole thread size designator: $1/4$ - 20 nc - 2 ; threaded hole qty: 1; threaded hole location: 90 deg. Clock wise from
keyway at 0.312" at center of bolt hole from hub end; securing method: threaded hole; keying facility qty: 1; counterbore location: coupling
end; thread provision: unthreaded; distance from center of bore to bottom of keyway: 0.484" min., 0.853" max.; keyway wd: 0.1875" min.,
0.1880" max.; counterbore dep.: 0.396" min., 0.416" max.; counterbore dia.: 1.302" min., 1.322" max.
Material:
Steel
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A521x0