NSN 3010-00-538-9813

Gearcase-motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3010-00-538-9813

Overall Height:					
23.250 inches					
Overall Length:					
33.500 inches					
Overall Width:					
20.125 inches					
Current Type:					
Ac input					
Duty Cycle:					
Continuous					
Inclosure Feature:					
Dripproof protected-45 deg					
Winding Type:					
Induction-squirrel cage					
Mounting Facility Type And Quantity:					
4 unthreaded hole					
Cooling Method:					
Natural convection ventilated					
Inclosure Specificationification:					
Mil-std-108					
Features Provided:					
Horizontal mounting position					
Power Rating:					
25.0000 horsepower output					
25.0000 horsepower output					
25.0000 horsepower output Center To Center Distance Between Mounting Facilities Parallel To Length:					
Center To Center Distance Between Mounting Facilities Parallel To Length:					
Center To Center Distance Between Mounting Facilities Parallel To Length: 12.250 inches Tempurature Rating:					
Center To Center Distance Between Mounting Facilities Parallel To Length: 12.250 inches Tempurature Rating: 40.0 operating degrees celsius and 55.0 ambient degrees celsius					
Center To Center Distance Between Mounting Facilities Parallel To Length: 12.250 inches Tempurature Rating:					
Center To Center Distance Between Mounting Facilities Parallel To Length: 12.250 inches Tempurature Rating: 40.0 operating degrees celsius and 55.0 ambient degrees celsius Center To Center Distance Between Mounting Facilities Parallel To Width: 14.000 inches					
Center To Center Distance Between Mounting Facilities Parallel To Length: 12.250 inches Tempurature Rating: 40.0 operating degrees celsius and 55.0 ambient degrees celsius Center To Center Distance Between Mounting Facilities Parallel To Width: 14.000 inches Connection Type And Voltage Rating In Volts:					
Center To Center Distance Between Mounting Facilities Parallel To Length: 12.250 inches Tempurature Rating: 40.0 operating degrees celsius and 55.0 ambient degrees celsius Center To Center Distance Between Mounting Facilities Parallel To Width: 14.000 inches					
Center To Center Distance Between Mounting Facilities Parallel To Length: 12.250 inches Tempurature Rating: 40.0 operating degrees celsius and 55.0 ambient degrees celsius Center To Center Distance Between Mounting Facilities Parallel To Width: 14.000 inches Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase:					
Center To Center Distance Between Mounting Facilities Parallel To Length: 12.250 inches Tempurature Rating: 40.0 operating degrees celsius and 55.0 ambient degrees celsius Center To Center Distance Between Mounting Facilities Parallel To Width: 14.000 inches Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase: Three input					
Center To Center Distance Between Mounting Facilities Parallel To Length: 12.250 inches Tempurature Rating: 40.0 operating degrees celsius and 55.0 ambient degrees celsius Center To Center Distance Between Mounting Facilities Parallel To Width: 14.000 inches Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase: Three input Frequency In Hertz:					
Center To Center Distance Between Mounting Facilities Parallel To Length: 12.250 inches Tempurature Rating: 40.0 operating degrees celsius and 55.0 ambient degrees celsius Center To Center Distance Between Mounting Facilities Parallel To Width: 14.000 inches Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input					
Center To Center Distance Between Mounting Facilities Parallel To Length: 12.250 inches Tempurature Rating: 40.0 operating degrees celsius and 55.0 ambient degrees celsius Center To Center Distance Between Mounting Facilities Parallel To Width: 14.000 inches Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input Terminal Type And Quantity:					
Center To Center Distance Between Mounting Facilities Parallel To Length: 12.250 inches Tempurature Rating: 40.0 operating degrees celsius and 55.0 ambient degrees celsius Center To Center Distance Between Mounting Facilities Parallel To Width: 14.000 inches Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input Terminal Type And Quantity: 3 solder lug					
Center To Center Distance Between Mounting Facilities Parallel To Length: 12.250 inches Tempurature Rating: 40.0 operating degrees celsius and 55.0 ambient degrees celsius Center To Center Distance Between Mounting Facilities Parallel To Width: 14.000 inches Connection Type And Voltage Rating In Volts: 440.0 line to neutral single input Phase: Three input Frequency In Hertz: 60.0 input Terminal Type And Quantity:					

N/a

NSN 3010-00-538-9813

Gearcase-motor - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A271a0

Mil-std (military Standard):

Mil-std-108 spec.