NSN 3010-00-556-8282

Gearcase-motor - Page 1 of 2

Overall Height: 3.656 inches Overall Length:



View Online at https://aerobasegroup.com/nsn/3010-00-556-8282

3.468 inches
Overall Width:
2.812 inches
Shaft Diameter:
0.2500 inches single end
Current Type:
Ac input
Shaft Rotation Direction:
Clockwise single end or counterclockwise single end
Duty Cycle:
Continuous
Inclosure Feature:
Totally enclosed
Mounting Method:
Flange
Mounting Facility Type And Quantity:
2 unthreaded hole
Geared Head Output Shaft Alignment Position:
Offset above parallel to shaft axis single end
Cooling Method:
Cooling Method: Nonventilated
•
Nonventilated
Nonventilated Torque Rating And Type:
Nonventilated Torque Rating And Type: 5.0 inch-ounces stalled
Nonventilated Torque Rating And Type: 5.0 inch-ounces stalled Inclosure Specificationification:
Nonventilated Torque Rating And Type: 5.0 inch-ounces stalled Inclosure Specificationification: Commercial
Nonventilated Torque Rating And Type: 5.0 inch-ounces stalled Inclosure Specificationification: Commercial Features Provided:
Nonventilated Torque Rating And Type: 5.0 inch-ounces stalled Inclosure Specificationification: Commercial Features Provided: Vertical mounting position and horizontal mounting position
Nonventilated Torque Rating And Type: 5.0 inch-ounces stalled Inclosure Specificationification: Commercial Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing:
Nonventilated Torque Rating And Type: 5.0 inch-ounces stalled Inclosure Specificationification: Commercial Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.656 inches single end
Nonventilated Torque Rating And Type: 5.0 inch-ounces stalled Inclosure Specificationification: Commercial Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.656 inches single end Tempurature Rating:
Nonventilated Torque Rating And Type: 5.0 inch-ounces stalled Inclosure Specificationification: Commercial Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.656 inches single end Tempurature Rating: -6.7 operating degrees celsius and 79.0 operating degrees celsius
Nonventilated Torque Rating And Type: 5.0 inch-ounces stalled Inclosure Specificationification: Commercial Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.656 inches single end Tempurature Rating: -6.7 operating degrees celsius and 79.0 operating degrees celsius Mounting Facility Circle Diameter:
Nonventilated Torque Rating And Type: 5.0 inch-ounces stalled Inclosure Specificationification: Commercial Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.656 inches single end Tempurature Rating: -6.7 operating degrees celsius and 79.0 operating degrees celsius Mounting Facility Circle Diameter: 3.188 inches
Nonventilated Torque Rating And Type: 5.0 inch-ounces stalled Inclosure Specificationification: Commercial Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.656 inches single end Tempurature Rating: -6.7 operating degrees celsius and 79.0 operating degrees celsius Mounting Facility Circle Diameter: 3.188 inches Connection Type And Voltage Rating In Volts:
Nonventilated Torque Rating And Type: 5.0 inch-ounces stalled Inclosure Specificationification: Commercial Features Provided: Vertical mounting position and horizontal mounting position Length Of Shaft From Housing: 0.656 inches single end Tempurature Rating: -6.7 operating degrees celsius and 79.0 operating degrees celsius Mounting Facility Circle Diameter: 3.188 inches Connection Type And Voltage Rating In Volts: 115.0 line to neutral single input

A1 single style single end

NSN 3010-00-556-8282

Gearcase-motor - Page 2 of 2



60.0 input

Terminal Type And Quantity:

4 solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A271a0