NSN 3010-00-640-4768

Shaft Coupling Half - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3010-00-640-4768

| Body Style: |
|--|
| Flexible keyway insert type, through bore |
| Overall Length: |
| 0.343 inches |
| Outside Diameter: |
| 1.000 inches |
| Bore Diameter: |
| 0.2500 inches |
| Bore Length: |
| 0.2800 inches |
| Bore Shape: |
| Straight |
| Special Features: |
| 5fsc application data: 1 radio receiver, except navigation, except airborne; surface treatment: passivated; distance from bore centerline to |
| body keying facility bottom/top: 0.250" nom.; body keying facility dep/ht: 0.063" nom.; body keying facility wd: 0.155" nom.; securing |
| method: compression mtd by means of 4 slots in hub 0.032" w by 0.218" deep, spaced 90 deg. Apart; keying facility and bore counterbore |
| feature: not included; hub od: 0.312" nom.; thread provision: unthreaded; flange thickness: 0.125" nom. |
| Material: |
| Steel |
| Material Specification: |
| An-s-771, grade composition fm assn standard single material response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A521x0 |
| |
| |