NSN 3010-00-682-7222



Rigid Shaft Coupling - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3010-00-682-7222 **Hole Diameter:** 1.005 inches **Spline Minor Diameter:** 0.7811 inches second end **Overall Length:** 3.250 inches **Spline Quantity:** 7 second end **Thread Size Designator:** 3/8-16 **Bore Diameter:** 1.1260 inches first end **Overall Diameter:** 2.000 inches **Bore Length:** 1.7500 inches first end **End Application:** Steam turbine **Bore Shape:** Straight first end Spline Pressure Angle In Deg: 30.000 second end Spline Length: 1.000 inches second end Spline Type: Straight or involute second end **Securing Method:** Threaded hole **Threaded Hole Quantity: Features Provided:** Keyway **Body Material:** Steel **Special Features:** Distance from center of bore to bottom of keyway: first end, 0.688 in.; pitch diameter: second end, 0.875 in.; 1 keying facility provided first end; keying facility width: first end, 0.250 in. **Style Designator:** Plain sleeve Shelf Life:

N/a

Unit Of Measure:

NSN 3010-00-682-7222

Rigid Shaft Coupling - Page 2 of 2



Demilitarization:

No

Fiig:

A522c0